

Beck & Jørgensen A/S  
Rosenkæret 25-29  
DK-2860 Søborg

Tel. +45 3953 0311  
Fax +45 3953 0340  
e-mail [bj@bj.dk](mailto:bj@bj.dk)  
Web [www.bj.dk](http://www.bj.dk)



**Interior woodwork**

## Waterborne industrial products for interior woodwork

Product	DK Sanding Primer Opaque	DK Sealing Primer Opaque	DK Interior Stain Transparent	DK UV-Filter Lye	DK Enamel Opaque and Clear	DK 1K PU Clear, high gloss
Product no./type	962/T222	963/T223	974	975/T265	976/T236	939
Description	Acrylic primer with good sanding properties.  Good adhesion and quick drying. Extremely easy to sand. Good undercoat for DK Enamel 976.	Acrylic primer with sealing effect.  Good adhesion and good sanding properties. Sealing properties against water-soluble colouring. Good undercoat for DK Enamel 976.	Interior stain based on a combination of acrylics and alkyds.  Can be used with or without a topcoat varnish such as DK 1K PU Clear High-Gloss 939.	Lye-coloured, UV-filtering acrylic lacquer.  Inhibits the natural yellowing of the wood and provides a dirt-repellent and cleaning-friendly surface.	Enamel paint based on acrylic binder.  Hard, resistant, non-yellowing film. Good resistance to common pH-neutral detergents, chemicals and fats. Suitable for drying at 35-45°C, which ensures quick blocking resistance.	One-component self cross linking clear lacquer based on polyurethanes and acrylics.  Gives a clear, high-gloss surface with excellent wood warming. The lacquer is hard and impact resistant, and is based on a low yellowing polyurethane and excellent filling.
Use	For indoor surfaces of wood or wood-based materials.	For indoor surfaces of wood or wood-based materials.	Stain for interior surfaces of wood or wood-based products.	For treating indoor ceiling and wall panelling, mouldings, etc. of fir, pine and other light wood varieties.	For indoor surfaces of solid wood or wood-based materials such as veneer, HDF, MDF and chipboard.	For indoor surfaces of solid wood or wood-based materials such as veneer, HDF, MDF and chipboard.
Application method	Spray	Spray	Dip Mechanical applicator Flow coat Spray	Mechanical applicator Spray Roller Paintbrush	Spray	Spray
Wet layer thickness	approx. 150 µm	approx. 150 µm	To the required appearance	To the required appearance	150-175 µm	10-125 µm
Gloss	Matt	Matt	Matt	10	40-45	approx. 90
Colour	White	White	Clear, transparent shades	Lye	White, clear <i>Both can be tinted</i>	Clear

The above information is for guidance only. Any coating task should be approached on the basis of actual conditions. Further information about the products is available on our website [www.bj.dk](http://www.bj.dk).

### Beck & Jørgensen and LARCO

Beck & Jørgensen was established in 1892. We manufacture and sell all kinds of coating materials for the woodworking industry and for professional painters and decorators. Our range of products is complemented by a wide range of accessories such as wallpaper, brushes and tools from suppliers who focus on high quality and functionality. LARCO is our brand name for a range of industrial products for indoor and outdoor woodwork. For more information, please contact your local sales consultant or customer centre.