

#### **SAFETY DATA SHEET**

## 101 Knastelak Vandig

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name

101 Knastelak Vandig

Product no.

101

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Spærrende grunder

Uses advised against

No special

## 1.3. Details of the supplier of the safety data sheet

#### Company and address

#### Beck & Jørgensen A/S

Rosenkaeret 25-29

DK-2860 Søborg

Denmark

Tel: +45 39 53 03 11

## Contact person

Mikael Jensen

E-mail

miljo@bj.dk

Revision

7/13/2022

**SDS Version** 

1.0

## 1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

#### SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

#### 2.2. Label elements

Hazard pictogram(s)

Not applicable

Signal word

Not applicable

Hazard statement(s)

Not applicable

Safety statement(s)

General

-

Prevention

-

Response



## Storage

Disposal

#### Hazardous substances

No special

#### 2.3. Other hazards

#### Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210, Safety data sheet available on request.

#### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### VOC

VOC content: 18 g/L

MAXIMUM VOC CONTENT (Phase II, category A/g (WB): 30 g/L)

## SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Titandioxid	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17 Index No.:	10-15%		
propane-1,2-diol	CAS No.: 57-55-6 EC No.: 200-338-0 REACH: 01-211945809-23 Index No.:	1-3%		
reaction mass of 5-chloro- 2-methyl-2H-isothiazol-3- one and 2-methyl-2H- isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: REACH: Index No.: 613-167-00-5	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)	
1,2-benzisothiazol-3(2H)- on	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: Index No.: 613-088-00-6	<0.0015%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	

-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

101 Knastelak Vandig Page 2 of 18



#### Other information

-

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

## Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### Burns

Not applicable

#### 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction to predisposed persons.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No special

#### Information to medics

Bring this safety data sheet or the label from this product.

#### SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2).

#### 5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements



#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

#### 6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

No specific requirements

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Titandioxid

Long term exposure limit (8 hours) (mg/m³): 6 (som Ti)

Annotations

K = Dusts that contain the substance on a respirable form are considered to be carcinogenic.

Statutory order 1054 on exposure limits for substances and mixtures (28/06/2022)

Titandioxid is included in the national list of substances suspected of causing cancer

BEK nr 1795 af 18/12/2015 om foranstaltninger til forebyggelse af kræftrisikoen ved arbejde med stoffer og materialer

#### DNEL

## propane-1,2-diol

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	213 mg/kg/day
Long term – Local effects - General population	Inhalation	10 mg/m3
Long term – Local effects - Workers	Inhalation	10 mg/m3
Long term – Systemic effects - General population	Inhalation	50 mg/m3
Long term – Systemic effects - Workers	Inhalation	168 mg/m3
Long term – Systemic effects - General population	Oral	85 mg/kg/day

### Titandioxid

101 Knastelak Vandig Page 4 of 18



	Duration	Route of exposure	DNEL
	Long term – Local effects - Workers	Inhalation	10 mg/m3
	Long term – Systemic effects - General population	Oral	700 mg/kg bw/day
PNEC	propane-1,2-diol		

Route of exposure	Duration of Exposure	PNEC
Freshwater	-	260 mg/l
Freshwater sediment	-	572 mg/kg
Intermittent release	-	183 mg/L
Marine water	-	26 mg/L
Marine water sediment	-	57,2 mg/kg
Sewage treatment plant	-	20000 mg/L
Soil	-	50 mg/kg

#### **Titandioxid**

Route of exposure	Duration of Exposure	PNEC
Freshwater	-	0,184 mg/l
Freshwater sediment	-	1000 mg/l
Intermittent release	-	0,193 mg/l
Marine water	-	0,0184 mg/l
Marine water sediment	-	100 mg/Kg
Sewage treatment plant	-	100 mg/l
Soil	-	100 mg/l

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

## General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

## **Exposure scenarios**

There are no exposure scenarios implemented for this product.

## **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

## Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

## Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements

## Individual protection measures, such as personal protective equipment Generally

101 Knastelak Vandig Page 5 of 18



Page 6 of 18

Only CE-marked personal protection equipment should be used. Use only CE marked protective equipment.

#### **Respiratory Equipment**

Work situation	Туре	Class	Colour	Standards	
Non industrial spraying	Combination filter A2P3	Class 2/3	Brown/White	EN14387	

## Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

#### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 60	EN374-2, EN374-3, EN388	

#### Eye protection

'		
Type	Standards	
Safety glasses	EN166	

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

White

Odour / Odour threshold

Testing not relevant or not possible due to nature of the product.

рΗ

3 - 4

Density (g/cm³)

1,34

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)



100

#### Vapour pressure

Testing not relevant or not possible due to nature of the product.

#### Relative vapour density

Testing not relevant or not possible due to nature of the product.

#### Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

#### Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to nature of the product.

### Ignition (°C)

Testing not relevant or not possible due to nature of the product.

#### Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

#### Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

#### Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

#### Solubility in fat (q/L)

Testing not relevant or not possible due to nature of the product.

#### 9.2. Other information

VOC (q/L)

18

## Other physical and chemical parameters

No data available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No data available

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

## 10.3. Possibility of hazardous reactions

No special

#### 10.4. Conditions to avoid

No special

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

## 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/substance Titandioxid

Test method

Species Rat
Route of exposure Oral
Test LD50



Result >5000 mg/Kg · Other information

Titandioxid

LC50

Product/substance Test method

**Species** Rat Inhalation Route of exposure

Result > 3,43 - 5,09 mg/l ·

Other information

Test

Product/substance

propane-1,2-diol

Test method

Species Rat Route of exposure Oral LD50 Test

Result 22000 mg/kg ·

Other information

Product/substance

propane-1,2-diol

Test method

Rabbit **Species** Route of exposure Dermal LD50 Test Result 2000 mg/kg ·

Other information

Product/substance propane-1,2-diol

Test method

Rabbit Species Route of exposure Inhalation Test LC50 Result 317 mg/l ·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species

Rat Route of exposure Oral LD50 Test

Result 49,6 - 75 mg/Kg ·

Other information

Product/substance

 $reaction\ mass\ of\ 5\text{-chloro-2-methyl-2H-isothiazol-3-one}\ and\ 2\text{-methyl-2H-isothiazol-3-one}\ (3:1)$ 

Test method

Rat Species Inhalation Route of exposure Test

0,33 mg/l, 4 h, aerosol · Result

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

101 Knastelak Vandig Page 8 of 18



Test method

Species Rabbit
Route of exposure Dermal
Test LD50

Result 200 - 1000 mg/Kg ·

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Rat
Route of exposure Oral
Test LD50
Result 1193 mg/Kg ·

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Rat
Route of exposure Dermal
Test LD50
Result 4115 mg/Kg ·

Other information

#### Skin corrosion/irritation

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method OECD 404 Species Rabbit

Duration

Result Adverse effect observed (Irritating)

Other information

## Serious eye damage/irritation

Product/substance 1,2-benzisothiazol-3(2H)-on Test method no guideline followed

Species Duration

Result Adverse effect observed (Causes serious eye damage)

Other information

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

## Skin sensitisation

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Human

Result Adverse effect observed (sensitising)
Other information Can course allergic reaction at skin contact

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

101 Knastelak Vandig Page 9 of 18



Species Human

Result Adverse effect observed (sensitising)
Other information Can course allergic reaction at skin contact

## Germ cell mutagenicity

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species

Conclusion No adverse effect observed

Other information

## Carcinogenicity

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species

Route of exposure

Target organ Duration Test

Result

Conclusion No adverse effect observed

Other information

#### Reproductive toxicity

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species Duration

Test Result

Conclusion No adverse effect observed

Other information

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### Long term effects

No special

## Endocrine disrupting properties

No special

#### Other information

Titandioxid has been classified by IARC as a group 2B carcinogen.

#### SECTION 12: Ecological information

#### 12.1. Toxicity



BS

Product/substance

Titandioxid

Titandioxid

Titandioxid

Algae

Test method

Species Fish

Compartment

Duration 96 hours Test LC50

Result >1000 mg/l·

Other information

Product/substance

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result >1000 mg/l·

Other information

Product/substance

Test method

Species Compartment

 $\begin{array}{ll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 61 \text{ mg/l} \cdot \end{array}$ 

Other information

Product/substance Test method propane-1,2-diol

Species

pecies Fish

Compartment

Duration 96 hours
Test LC50

Result  $> 40613 \text{ mg/l} \cdot$ 

Other information

Product/substance

propane-1,2-diol

Test method Species

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result 18800 mg/l·

Other information

Product/substance

propane-1,2-diol

Test method

Species Algae

Compartment

Duration 96 hours
Test EC50
Result 19000 mg/l·

101 Knastelak Vandig Page 11 of 18



#### Other information

Product/substance

propane-1,2-diol

Test method

Species

Algae

Compartment

72 hours Duration Test EC50 Result 24200 mg/l ·

Other information

Product/substance Test method

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Species Fish

Compartment

96 hours Duration Test LC50 Result 0,19 mg/l ·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Test method

**Species** 

Compartment

Daphnia

48 hours Duration EC50 Test Result 0,10 mg/l ·

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

**Species** 

Algae

Compartment

Duration 72 hours EC50 Test 0,048 mg/l· Result

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Algae

Daphnia

Species Compartment

Duration 96 hours NOEC Test Result 0,032 mg/l ·

Other information

Product/substance

Test method

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Species Compartment

Duration 21 days

101 Knastelak Vandig Page 12 of 18



Test EC50 Result > 1 mg/l ·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Fish Species

Compartment

Duration 96 hours Test LC50 0,58 mg/l · Result

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Fish **Species** 

Compartment

Duration 34 d. Test NOEC Result 0,5 mg/l ·

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Algae

Compartment

Duration 48 hours Test NOEC

0,00064 mg/l · Result

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Compartment

Species

Duration 21 days Test NOEC 0,004 mg/l · Result

Daphnia

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Fish

Compartment

Species

Duration 28 days Test NOEC 0,098 mg/l · Result

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

**Species** Algae

101 Knastelak Vandig Page 13 of 18



Compartment

 $\begin{array}{lll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{NOEC} \\ \text{Result} & 0,0012 \text{ mg/l} \cdot \end{array}$ 

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Fish

Compartment

Duration 96 hours
Test LC50
Result 1,3 mg/l·

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Daphnia

Compartment

 $\begin{array}{ll} \text{Duration} & 96 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 1,5 \text{ mg/l} \cdot \end{array}$ 

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Algae

Compartment

 $\begin{array}{lll} \text{Duration} & 48 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 0,055 \text{ mg/l} \cdot \end{array}$ 

Other information

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result 2,94 mg/l·

Other information

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 24 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 0,11 \text{ mg/l} \cdot \end{array}$ 

Other information

Product/substance 1,2-benzisothiazol-3(2H)-on

101 Knastelak Vandig Page 14 of 18



Test method

Species Fish

Compartment

Duration No data available.

Test NOEC Result 0,21 mg/l·

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Daphnia

Compartment

Duration 21 days
Test NOEC
Result 1,2 mg/l·

Other information

## 12.2. Persistence and degradability

Product/substance propane-1,2-diol

Biodegradable Yes

Test method

Result BOD5/COD > 0,5

Product/substance 1,2-benzisothiazol-3(2H)-on

Biodegradable
Test method

e Yes

Test method Result

## 12.3. Bioaccumulative potential

Product/substance propane-1,2-diol

Test method

Potential No

bioaccumulation

LogPow -1,4000 BCF 0,09

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Potential No

bioaccumulation

LogPow 0,4000 BCF 3,6

Other information

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method

Potential No

bioaccumulation

LogPow 1,3000

BCF No data available

101 Knastelak Vandig Page 15 of 18



#### Other information

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. Endocrine disrupting properties

No special

#### 12.7. Other adverse effects

No special

#### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

## EWC code

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

#### Specific labelling

Not applicable

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

### **SECTION 14: Transport information**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

<sup>\*</sup> Packing group

#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

#### 14.6. Special precautions for user

Not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available

#### SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Restrictions for application

No special

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

#### Additional information

Code number (1993): 00-1.

Sources

<sup>\*\*</sup> Environmental hazards



Executive Order no. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car repair painting.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on

classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H330, Fatal if inhaled.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

## Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number



SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

Not applicable

#### The safety data sheet is validated by

XXX

## Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en