

# 118 Wall Filler Medium, Low Density



## Product information

Beck & Jorgensen A/S

### Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

### Cleaning instructions

Water

### Safety & environment

Use eye and respiratory protection according to environmental rules, and read MSDS for further instructions.

### Remarks

High film layer prolongs drying time

### Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless	31-35 Graco			

## Technical data

<b>Binder:</b>	Vinylacrylate copolymer
<b>Type:</b>	Low Density Filler
<b>Gloss:</b>	
<b>Vol. dry:</b>	
<b>Colours:</b>	
<b>Drying:</b>	App. 8-10 hours depending on layer, temperature and humidity
<b>Application:</b>	
<b>Thinning:</b>	Water. Normally not to be diluted
<b>Coverage:</b>	Aproxx 1 ltr./m <sup>2</sup> /mm
<b>Tools:</b>	Spartula, roller or heavy duty spray equipment
<b>Mal-Code:</b>	00-1 (1993)

