

119 Wall Filler Coarse, Low Density



Product information

Beck & Jorgensen A/S

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Water

Safety & environment

Use eye and respiratory protection according to environmental rules, and read MSDS for further instructions.

Remarks

High film layer prolongs drying time

Sprayguide

| Spraying | Nozzle | Air pressure | Ass. Air | Filter |
|----------|-------------|--------------|----------|--------|
| Airless | 31-35 Graco | | | |

Technical data

| | |
|---------------------|------------------------------------------------|
| Binder: | Vinylacrylate copolymer |
| Type: | Low Density Filler |
| Gloss: | |
| Vol. dry: | |
| Colours: | Grey |
| Drying: | Aprox 1 hour / mm at 20C og 65% RH |
| Application: | +10 °C to + 25° C. RH: 40-80% |
| Thinning: | Water. Normally not to be diluted |
| Coverage: | Aprox 1 ltr./m ² /mm |
| Tools: | Spartula, roller or heavy duty spray equipment |
| Mal-Code: | 00-1 (1993) |

