

### Product Description

Effective means of cleansing, refreshing and whitening of woodwork as. spruce, pine and larch. Used with or without subsequent treatment with woodcare products or Wood oil.

### Directions for use

The surface should be cleaned of dust and dirt by thorough washing with clean water and a stiff brush. Wood Freshener 127 diluted with water 1 part Wood Freshener to 5-10 parts water, by strong discoloration you can use the Wood Freshener undiluted if needed. After a couple of hours to 24 hours, wash off with water and a stiff brush. Heavily infested areas can with advantage be retried.

### Cleaning instructions

Water

### Safety & environment

Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Remarks

As the product contains active substances, subsequent washing with pure water is required.

## Technical data

<b>Binder:</b>	Benzalkonium Chloride, Oxalic Acid and cleaning chemicals
<b>Type:</b>	
<b>Gloss:</b>	
<b>Vol. dry:</b>	
<b>Colours:</b>	Colourless
<b>Drying:</b>	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
<b>Application:</b>	+10 °C to + 25° C. RH: 40-80%
<b>Thinning:</b>	Water
<b>Coverage:</b>	2-8 m <sup>2</sup> /ltr
<b>Tools:</b>	brush and roller
<b>Mal-Code:</b>	

