

Product Description

Elastoplastic acrylic sealant for joints around doors, windows and elements on joints from 0-25 mm. Also for joints and cracks in concrete, wood and plaster.

The product has a good adhesion to building materials such as masonry, concrete and painted wood

The sealant has an elasticity of approx. 15%.

B&J Acrylic Sealant can be used both in- and outdoors but should be painted for outdoor use. The surface should likewise be protected from rain during drying. . The product is not suitable for places where there is constant water vapor or on surfaces such as PE, PP, Teflon and asphalt surfaces. In case of doubt, a test field should be performed.

Directions for use

The surfaces must be dry and clean and free of dust and loose particles. Apply the sealant with a hand gun, and level the joint with a wet sponge or jointing stick.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Personal protection equipment must be used. For information regarding safety, health and environment see Material Safety Data Sheet (MSDS) at www.bj.dk.

Technical data

Binder:	Acrylic polymer
Type:	Acrylic Sealant
Gloss:	App. 5, matt
Vol. dry:	
Colours:	White
Drying:	1-4 hours at 20° C. RH.: 65%. Recoatable after app. 24 hours.
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Not to be thinned
Coverage:	Aproxx 1 ltr./m ² /mm
Tools:	Hand gun
Mal-Code:	00-1 (1993)

