

### Product Description

Elastoplastic acrylic sealant for joints around doors, windows and elements on joints from 0-25 mm. Also for joints and cracks in concrete, wood and plaster.

The product has a good adhesion to building materials such as masonry, concrete and painted wood

The sealant has an elasticity of approx. 15%.

B&J Acrylic Sealant can be used both in- and outdoors but should be painted for outdoor use. The surface should likewise be protected from rain during drying. . The product is not suitable for places where there is constant water vapor or on surfaces such as PE, PP, Teflon and asphalt surfaces. In case of doubt, a test field should be performed.

### Directions for use

The surfaces must be dry and clean and free of dust and loose particles. Apply the sealant with a hand gun, and level the joint with a wet sponge or jointing stick.

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Safety & environment

Personal protection equipment must be used. For information regarding safety, health and environment see Material Safety Data Sheet (MSDS) at [www.bj.dk](http://www.bj.dk).

### Technical data

<b>Binder:</b>	Acrylic polymer
<b>Type:</b>	Acrylic Sealant
<b>Gloss:</b>	App. 5, matt
<b>Vol. dry:</b>	
<b>Colours:</b>	White
<b>Drying:</b>	1-4 hours at 20° C. RH.: 65%. Recoatable after app. 24 hours.
<b>Application:</b>	+10 °C to + 25° C. RH: 40-80%
<b>Thinning:</b>	Not to be thinned
<b>Coverage:</b>	Aproxx 1 ltr./m <sup>2</sup> /mm
<b>Tools:</b>	Hand gun
<b>Mal-Code:</b>	00-1 (1993)

