

Product Description

Durable water-based 1 comp. acrylic floor paint.

The product can be used indoors for floors with medium wear, such as housing, offices and other areas where you want extra durability and easy maintenance. PU Floor Paint can be used on stable wood and concrete floors

Directions for use

The surface must be clean, dry and sound and free from all loose material.

New concrete and wood should be primed with adequate primer, and knots with special primer.

Previously painted surfaces should be clean, dry and sound and free from all loose paint and sanded to adhesion.

Cleaning instructions

Cleaning with water, preferably added a detergent.

Safety & environment

Brush / Roller: Working clothes, PU-gloves and protective glasses.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glasses. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Technical data

Binder:	1 comp. acrylic
Type:	
Gloss:	Approx. 30, semigloss
Vol. dry:	
Colours:	White, Ral 7035 and B&J tinting system
Drying:	Approx. 2 hours, recoatable after approx. 24 hours, fully cured after 5-7 days (+20°C, RH: 60%)
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water. Normally not to be diluted
Coverage:	6-8 m ² /ltr
Tools:	Roller with short pile or brush
Mal-Code:	00-1 (1993)

