

Product Description

Durable water-based polyurethane / acrylic floor paint.

The product can be used indoors for floors with medium wear, such as housing, offices and other areas where you want extra durability and easy maintenance. PU Floor Paint can be used on stable wood and concrete floors.

Directions for use

The surface must be clean dry and sound and free from all loose material.

New concrete and wood should be primed with adequate primer, and knots with special primer.

Previously painted surfaces should be clean dry and sound and free from all loose paint and sanded to adhesion.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Technical data

Binder: Acrylic / Polyurethane Aqueous

Type:

Gloss: Approx. 50 semi-gloss

Vol. dry:

Colours: White and Clear. Can be tinted

Drying:

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water. Normally not to be diluted

Coverage: Rough saw timber: 2-5 m²/Liter

Planed timber: 8-10 m²/Liter

Tools: Short nap roller or brush

Mal-Code: 00-1 (1993)

