

Product Description

High quality wall paint with excellent coverage and low odour interior paint with excellent cleaning properties and resistant surface.

The product is suitable for most use in domestic houses, as living rooms and kitchens as well as in offices, where a dull matt appearance is required.

Wet scrub Class 1, EN 13300, Emmisonstested M1 (EMCBM).

B&J 0 fulfills the requirements the EU Eco-label in all colours if tinted within the B&J tintingsystem Monicolor.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Acrylic

Type:

Gloss: Approx. 1-2, Dull matt

Vol. dry:

Colours: White, NCS-S 0500 and B&J Tinting system

Drying: 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water

Coverage: 8-10 m²/ltr

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

