

Product Description

CARE 5 is Low odor wall paint, approved by the Danish Asthma Allergic federation.

The product does not contain any in can biocides or other harmful or allergenic substances.

CARE 5 is suitable for living room, offices, schools and kindergartens, where utmost consideration to allergic persons is to be taken.

Wet scrub Class 1 (EN13300), emission class M1 (EMCBM), DGNB 100 TLP-point

Directions for use

The substrate must be clean, dry and sound and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.

Priming of porous and water absorbing surfaces with CARE 5 thinned with 20% water.

Cleaning instructions

Water

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

This product is developed under the criterieas and control of the Danish Asthma Allergic foundation.

Further information to be found on www.denblåkrans.dk

Technical data

Binder:	Self crosslinking styrene acrylic
Type:	Acrylic wall paint
Gloss:	App. 5, matt
Vol. dry:	
Colours:	White, not to be tinted.
Drying:	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water
Coverage:	8-10 m ² /ltr
Tools:	Brush, roller or airless
Mal-Code:	

