

Product Description

Low-odor acrylic wall paint, with a high filling capacity on non-woven fiberglass and good adhesion on, e.g., plaster and concrete. The product can be used as a primer and finish paint on woven and non-woven fiber glass. The product is suitable for most use in domestic houses, as living rooms and childrens rooms, with a good cleanable surface.

The product fullfills the requierments the EU Eco-label in all colours if tinted within the B&J tintingsystem Monicolor.

Directions for use

The substrate must be clean, dry and sound and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 is recommended.

Cleaning instructions

Cleaning with water, preferably added a detergent.

Safety & environment

Brush / Roller: Working clothes, PU-gloves and protective glasses.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glasses. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

This product has been qualified for the EU Ecolabel by reducing the use of water and air pollution as well as the quantity of waste.

Further information on why this product was assigned with EU Ecolabel can be found on www.ecolabel.eu

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Self crosslinking styrene acrylic

Type: Acrylic wall paint

Gloss: App. 5, matt

Vol. dry:

Colours: White, Off white, NCS-S 0500 and B&J tinting system

Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.

Application: +10° C to +25° C. RH: 40-65%

Thinning: Water

Coverage: 8-10 m²/ltr

Tools: Brush, roller or airless

Mal-Code: