

457 Acrylic Wall Paint Gloss 7



Product information

Beck & Jørgensen A/S

Product Description

Advanced acrylic paint with good coverage and high filling of woven and nonwoven fiberglass.

Excellent adhesion to quality readymade wall filler.

The product is suitable for most use in domestic houses, as living rooms and kitchens as well as in offices.

Wet scrub Class 1, EN 13300.

Directions for use

The substrate must be clean, dry and sound and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.

Priming of porous and water absorbing surfaces with Microprimer 716 is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Self crosslinking styrene acrylic

Type: Acrylic wall paint

Gloss: Approx 7, Matt

Vol. dry:

Colours: White, Off white, NCS-S 0500 and B&J tinting system in light shades

Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water

Coverage: Approx. 4-8 m²/ltr.

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

