

Product Description

Mat high durable pit for facade with fine structure.
For facades of concrete, plaster and previously painted facades.
The products give a high filling capacity and a high gloss and colour retention.

Contains materials, that protect the film against surface mold.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.
Crack and holls shall be repaired with filler.
Priming of porous and water absorbing surfaces with Microprimer 716 or semilar is recommended.

Iron and metal shall be sufficiently primed before painting.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.
Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
----------	--------	--------------	----------	--------

Technical data

Binder:	Acrylic
Type:	Acrylic facade paint / Acrylic Wall paint
Gloss:	Approx. 3 Flat matt
Vol. dry:	Aprox 38%
Colours:	White and Clear. Can be tinted
Drying:	App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water. Normally not to be diluted
Coverage:	Rough saw timber: 2-5 m ² /Liter Planed timber: 8-10 m ² /Liter
Tools:	Brush, roller or airless
Mal-Code:	00-1 (1993)

