

Product Description

Priming Oil for priming of windows, exterior doors, façade claddings, eaves boards and the like. Based on alkyd and natural oil and containing material that protects against mold.

Directions for use

The surface must be dry clean and stable. Wood moisture should not exceed 18% RH. Any resin exudations to be removed and after drying with a suitable thinner. The product is thoroughly stirred before and during use.

Note that end grains and joinings are particularly absorbent and should therefore be treated with extra care and in abundant quantities.

The product may be diluted with up to 50% appropriate thinner

Cleaning instructions

White Spirit or "Brush Cleaner"

Safety & environment

Brush / Roller: Working close, Nitrill-gloves and protective glass and A2 mask.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

The product contains non drying oil, meaning waste and tools shall be in a closed container, due to flameability.

Technical data

Binder:	Alkyd and natural oil
Type:	
Gloss:	
Vol. dry:	
Colours:	Clear
Drying:	6-8 hours, recoatable after 24 hours at 20 ° C 65% RH
Application:	+5° C to +25° C. RF: 40-80%
Thinning:	White spirit
Coverage:	5-10 m ² /ltr. Depending on the absorption
Tools:	Brush, Dipping
Mal-Code:	2-1 (1993)

