

505 B3 Semi Transp. Wood Protection



Product information

Beck & Jorgensen A/S

Product Description

Traditional Semi transparent wood based on alkyd oil. Contains agents that protect the coating against fouling. The product has an excellent penetration into the wood, creating a hydrophobic surface that stabilizes and prevents shrinkage cracks in the wood. Added UV absorber, which together with the pigmentation protects against the sun's harmful ultraviolet rays. For the same reason, the product should not be used as a colorless treatment. Contains materials, that protect the film against surface mold.

Directions for use

New Treatment:

The substrate must be clean, dry and stable and glossy surfaces sanded matt. Resin and knots should be degreased with appropriate solvent.

Exterior woodwork, of a type which can be degraded by wood-destroying fungi should be primed with 130 WB Wood Primer before finishing with 505 B3 Semi Transparent Woodcare 2-3 times.

Pressure and vacuum impregnated wood of good sound quality can be after drying treated directly with 505 B3 Semi Transparent Woodcare.

End grain should be saturated thoroughly with 130 WB Wood Primer before further end treatment.

maintenance:

The substrate must be clean, dry and sustainable and glossy surfaces sanded matt. Resin and knots should be degreased with appropriate solvent.

Areas with surface fouling should be treated with a suitable cleaning agent. Areas of bare wood should be primed with 130 WB Wood Primer prior to final treatment with 2-3 times with 505 B3 Semi Transparent Woodcare.

Local areas that are cleaned to scratch should be repaired with 505 B3 Semi Transparent Woodcare in the original colour prior to final treatment performed 2-3 times the entire surface

Cleaning instructions

White Spirit or "Brush Cleaner"

Safety & environment

Brush / Roller: Working close, Nitrill-gloves and protective glass and A2 mask.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

The product contains non drying oil, meaning waste and tools shall be in a closed container, due to flameability.

Technical data

Binder:	Alkyd and natural oil
Type:	Woodstain, Semi transparent
Gloss:	
Vol. dry:	
Colours:	Clear, can be tinted in transparent shades
Drying:	6-8 hours, recoatable after 24 hours at 20 ° C 65% RH
Application:	+5° C to +25° C. RF: 40-80%
Thinning:	Not to be thinned
Coverage:	5-10 m ² /ltr. Depending on the absorption
Tools:	Brush, Roller or Spraying
Mal-Code:	2-1 (1993)

