

## Product information

Beck & Jorgensen A/S

### Product Description

Hard and durable polyurethane / crosslinking acrylic enamel for interior use.  
Excelent for woodwork and primed metal, where an extra tough surface is needed.

### Directions for use

The substrate must be sound/stable, dry, clean, and free from all substances that may prevent good adhesion.  
New wood should be primed with suitable water-borne primer. If necessary, use a suitable undercoat, followed by 2 coats of PU Enamel  
Previously painted surfaces to be prepared suitable before applying the top coat. Iron and metal should be primed with suitable primer before applying the top coat.

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.  
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.  
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.  
Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Remarks

This product has been qualified for the EU Eco-label by reducing the water and airpolluttion as well as the quantity of waste.  
Further information on why this product was assigned with EU Eco-label can be found on [www.ecolabel.eu](http://www.ecolabel.eu)

### Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless with Finefinish	10-14 (graco)			100 mesh

### Technical data

**Binder:** Polyurethane and crosslinking acrylic  
**Type:**  
**Gloss:** Approx. 30, semigloss  
**Vol. dry:** App. 35%  
**Colours:** White and B&J tinting system  
**Drying:** 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF  
**Application:** +10 °C to + 25° C. RH: 40-80%  
**Thinning:** Water  
**Coverage:** 8-10 m<sup>2</sup>/ltr  
**Tools:** Brush, Roller or Spraying  
**Mal-Code:** 00-1 (1993)

