

Product information

Beck & Jorgensen A/S

Product Description

Hard and durable polyurethane / crosslinking acrylic enamel for interior use.
Excellent for woodwork and primed metal, where an extra tough surface is needed.

Directions for use

The substrate must be sound/stable, dry, clean, and free from all substances that may prevent good adhesion.
New wood should be primed with suitable water-borne primer. If necessary, use a suitable undercoat, followed by 2 coats of PU Enamel.
Previously painted surfaces to be prepared suitable before applying the topcoat. Metallic surfaces should be primed with suitable primer before applying the topcoat.

Cleaning instructions

Cleaning with water, preferably added a detergent.

Safety & environment

Brush / Roller: Working clothes, PU-gloves and protective glasses.
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.
Sanding: Working clothes, PU-gloves and protective glasses. P2 mask with air supply when needed.
Further information and MSDS on www.bj.dk

Remarks

This product has been qualified for the EU Ecolabel by reducing the use of water and air pollution as well as the quantity of waste.
Further information on why this product was assigned with EU Ecolabel can be found on www.ecolabel.eu

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless with Finefinish	10-14 (graco)			100 mesh

Technical data

Binder: Polyurethane and crosslinking acrylic
Type:
Gloss: Approx. 80, gloss
Vol. dry: App. 35%
Colours: White and B&J tinting system
Drying: 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
Application: +10 °C to + 25° C. RH: 40-80%
Thinning: Water
Coverage: 8-10 m²/ltr
Tools: Brush, Roller or Spraying
Mal-Code: 00-1 (1993)

