

703 Adhesive for wall covering



Product information

Beck & Jorgensen A/S

Product Description

Adhesive for wall covering of woven and non woven glass covering.
For gypsum board, plaster and concrete in dry rooms.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion, and old wall covering.

Remove dirt, dust and loose material and wash down the surface with appropriate detergent.

Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Apply the adhesive carefully in smooth and sufficient layer.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Polyvinylacetate

Type: Adhesive for wall covering

Gloss:

Vol. dry:

Colours:

Drying: 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Not to be thinned

Coverage: 4-6 m²/ltr

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

