

### Product Description

Microprimer for porous and absorbing surfaces. Anti-dripping effect and very good penetration on surfaces as plaster, filler concrete and similar.

For interior use and to be painted with most acrylic and pva paints.

### Directions for use

The substrate must be clean, dry and sound and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent, before priming with Microprimer 716.

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Technical data

<b>Binder:</b>	Acrylic
<b>Type:</b>	Micro Porous primer
<b>Gloss:</b>	
<b>Vol. dry:</b>	
<b>Colours:</b>	
<b>Drying:</b>	Approx. 1 hour, recoatable after approx. 4 hours at 20 °C, 65% RF.

<b>Application:</b>	+10 °C to + 25° C. RH: 40-80%
<b>Thinning:</b>	Water. Normally not to be diluted
<b>Coverage:</b>	Approx. 4-8 m <sup>2</sup> /ltr.
<b>Tools:</b>	brush and roller
<b>Mal-Code:</b>	00-1 (1993)

