

Product Description

Alkyd primer for interior use on porous and absorbing surfaces. Excellent penetration on absorbing and chalky surfaces. To be painted with most common wall paints

Directions for use

The substrate must be clean, dry and sound and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent, before priming wet-in-wet if needed.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

Not to be used on alkaline surfaces.

Technical data

| | |
|---------------------|--|
| Binder: | Alkyd emulsion |
| Type: | Alkyd primer Water based |
| Gloss: | |
| Vol. dry: | |
| Colours: | Colourless |
| Drying: | App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours. |
| Application: | +10 °C to + 25° C. RH: 40-80% |
| Thinning: | Water. Normally not to be diluted |
| Coverage: | Approx. 4-8 m ² /ltr. |
| Tools: | brush and roller |
| Mal-Code: | |

