

Product information

Beck & Jorgensen A/S

Product Description

Microprimer for porous and absorbing surfaces. Very good penetration on surfaces as plaster, filler concrete and similar.

For in- and exterior use and to be painted with most acrylic and pva paints.

Directions for use

The substrate must be clean, dry and sound and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material.

Wash down previously painted surfaces with appropriate detergent, before priming with Microprimer

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass. Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed. Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed. Further information and MSDS on www.bj.dk

Remarks

This product has been qualified for the EU Eco-label by reducing the water and airpoluttion as well as the quantity of waste.

Further information on why this product was assigned with EU Eco-label can be found on www.ecolabel.eu

Technical data

Binder: Type: Gloss:	Acrylic Micro Porous primer Avoid film forming layers when priming
Vol. dry: Colours: Drying:	Transparent blue Approx. 1 hour, recoatable after approx. 4 hours at 20 °C, 65% RF.
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water. Normally not to be diluted
Coverage:	Approx. 4-8 m²/ltr.
Tools:	Brush or roller
Mal-Code:	00-1 (1993)



Page: 1/1

Rev. date: 23.05.2023

This product information is based on both practical and laboratory tests and is a guidance to choice of product and working method. Always use the latest version of the product information, which can be found on www.bj.dk. As we don't know about the workers working conditions, we do not bear responsibility for the final result.