

718 Let Medium Ready mixed Filler



Product information

Beck & Jørgensen A/S

Product Description

Inreior use in dry rooms

All round filler for initial filling, thin smoothing filling and joint filling.

The product has a good filling capacity, easy to work with and easy to sand.

Suiteable for most surfaces in new constructions and renovation. When working on plasterborads, follow recomandations in accordance with EN-13963.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.

Priming of porous and water absorbing surfaces with Microprimer 716 or semilar is recommended.

Cleaning instructions

Water

Safety & environment

Use eye and respiratory protection according to enviromantal rules, an read MSDS for futher instructions.

Remarks

High film layer prolongs drying time

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless	31-35 Graco			

Technical data

Binder: Co-polymer dispersion

Type: Low Denisty Filler

Gloss:

Vol. dry:

Colours: Grey

Drying: App. 8-10 hours depending on layer, temperature and humidity

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water. Normally not to be diluted

Coverage: Aproxx 1 ltr./m²/mm

Tools: Spartula, roller or heavy duty spray equipment

Mal-Code: 00-1 (1993)

