

Product information

Beck & Jorgensen A/S

Product Description

High solid first coat for walls of plaster, glass fabrics or solid wall filler.
Also to be used as finish coat in secondary rooms.

Suitable for plaster, wall covering and wall filler

When used on Wall filler, this has to be of good and, stable quality and well dried. Test must be made.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Self crosslinking styrene acrylic

Type:

Gloss: App. 5, matt

Vol. dry:

Colours: Off White and NCS 0500 N

Drying: 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water

Coverage: Approx. 4-8 m²/litr.

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

