

729 Wall Filling Paint, Fine Structure



Product information

Beck & Jørgensen A/S

Product Description

High viscous wall paint for filling uneven surfaces.
For interior use, where structure is wanted

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended. Apply with roller and make the wanted structure with roller og block brush

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.
Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
----------	--------	--------------	----------	--------

Technical data

Binder: Polyvinylacetate
Type: Wall Filling Paint
Gloss: Approx. 3 Flat matt
Vol. dry:
Colours: White
Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.
Application: +10 °C to + 25° C. RH: 40-80%
Thinning: Water
Coverage: Aprox. 3-4 m²/ltr
Tools: Brush, roller or airless
Mal-Code: 00-1 (1993)

