

# 731 Interior Lye Lacquer



## Product information

Beck & Jørgensen A/S

### Product Description

Semi matt Lye lacquer, where a cleanable surface is wanted.

For interior woodwork and ceilings.

Also as stain for floors before lacquering with water based floor lacquer.

### Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.

Priming of porous and water absorbing surfaces with lacquer thinned 5-10 % water

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless with Finefinish	10-14 (graco)			100 mesh

### Technical data

**Binder:** Acrylic

**Type:** Acrylic

**Gloss:** Approx. 10, semi matt

**Vol. dry:** approx. 31%

**Colours:** Imitated Lye

**Drying:** 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF

**Application:** +10 °C to + 25° C. RH: 40-80%

**Thinning:** Water

**Coverage:** 8-10 m<sup>2</sup>/ltr

**Tools:** Brush or spray

**Mal-Code:** 00-1 (1993)

