

Product Description

Primer for walls in humid rooms of plaster, concrete, plasterboard etc.
Has to be painted.

Directions for use

Remove dirt, dust and loose material.
Wash down previously painted surfaces with appropriate detergent.
Priming of porous and waterabsorbing surfaces with Mikrodispers 716 is recommended.
Apply with roller og brush , min 150 gram per square meter

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.
Further information and MSDS on www.bj.dk

Remarks

For futher working instructions, please contact B&J Tecnicl Department.
Use eyeprotection and mask when sanding.

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Vinylacrylate copolymer
Type: Primer for humid rooms
Gloss: Approx. 50 semi-gloss
Vol. dry: Apros 45%
Colours: Transparent green
Drying: Aprox 4 hours at 20 °C 65% RH
Application: +10 °C to + 25° C. RH: 40-80%
Thinning: Water
Coverage:
Tools: Brush, roller or airless
Mal-Code: 00-1 (1993)

