

737 Wet Room Adhesive



Product information

Beck & Jorgensen A/S

Product Description

The adhesive is a part of B&J Bathroom system. Information on www.bj.dk
Adhesive for wall covering of woven and non woven glass covering.
For gypsum board, plaster and concrete in dry rooms.

Directions for use

Indoors for woven and non woven glass covering on plasterboard, plaster, concrete and painted surfaces.
Absorbent and porous substrates are primed with Wet Room Primer 736 diluted with water (1 part primer to 3 parts water). The primer must be completely dry before the next application.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Personal protection equipment must be used. For information regarding safety, health and environment see Material Safety Data Sheet (MSDS) at www.bj.dk.

Remarks

For further working instructions, please contact B&J Technical Department.
Use eyeprotection and mask when sanding.

Sprayguide

| Spraying | Nozzle | Air pressure | Ass. Air | Filter |
|--------------------|---------------|--------------|----------|--------|
| Airless and roller | 17-21 (Graco) | | | 60mesh |

Technical data

Binder:

Type: Adhesive, wet rooms

Gloss:

Vol. dry:

Colours: Colourless

Drying: 2-4 hours, recoatable after approx 24 hours at 20 °C 60% RH

Application: +10° C to +25° C. RH: 40-65%

Thinning: Water

Coverage:

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

