

738 Humid room paint, Vådrumsmaling



Product information

Beck & Jorgensen A/S

Product Description

Vådrumsmaling 738 is based on an advanced acrylic binder for humid rooms, industrial kitchens, factories and the pharmaceutical industry.

The product is suitable for concrete, gypsum board, plaster etc.

The paint gives a strong and resistant surface and a part of B&J Bathroom system. Information on www.bj.dk

Contains materials, that protect the film against surface mold.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.

Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

For further working instructions, please contact B&J Technical Department.

Use eye protection and mask when sanding.

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Acrylic

Type: Acrylic wall paint

Gloss: Approx. 40 Semi gloss

Vol. dry: Aprox 38%

Colours:

Drying: 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water. Normally not to be diluted

Coverage: Approx. 10 m²/ltr on planed wood

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

