### 741 ISO-DAN 5, Wall Paint



### **Product information**

### Beck & Jorgensen A/S

#### **Product Description**

Highly insulating paint with good coverage and low odour.

ISO 5 has an excellent insolation effect on nicotine, soot, lignin and dried up water stains.

The product I suitable for walls ceilings and interior stable woodworks.

Best effect is obtained with two layers with sufficient drying between each layer.

#### **Directions for use**

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.

Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Best effect is obtained if the substrate is thoroughly dry.

#### Cleaning instructions

Water

#### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

#### Remarks

High humidity do have a negative effect on the insulating properties.

Do not mix this product with other paints

Tools and spray equipment must be thoroughly cleaned with water

This product has been qualified for the EU Eco-label by reducing the water and airpoluttion as well as the quantity of waste.

Further information on why this product was assigned with EU Eco-label can be found on www.ecolabel.eu

Spravquide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Walls and ceilings	17-21 Graco/green	80-200 bar		60 mesh / black

#### **Technical data**

Binder: Acrylic with stain insulating effect

Type: Acrylic, Insulating Gloss: App. 5, matt

Vol. dry:

Colours: White

**Drying:** 6-8 hours, recoatable after 12 hours at 20 ° C and 65% RH

**Application:** +10 °C to + 25° C. RH: 40-80% **Thinning:** Water. Normally not to be diluted

Coverage: 8-10 m<sup>2</sup>/ltr

Tools: Brush, roller or airless

**Mal-Code:** 00-1 (1993)





# 741 ISO-DAN 5, Wall Paint



### **Product information**

## Beck & Jorgensen A/S

1 '11'	10 11 0	00 100 1	00   /  -     -
l wooden ceilings	l 12-14 Graco/green	80-120 bar	l 60 mesh / black l
Wooden cennigo	12 14 01000/910011	00 120 001	oo moon / black

Rev. date: 19.01.2021 - 2 Page: 2/2