

SAFETY DATA SHEET

754-xxx Cover It

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

754-xxx Cover It

Product no.

754101

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Plastalkyd vinduesmaling

Uses advised against

No special.

1.3. Details of the supplier of the safety data sheet

Company and address

Beck & Jørgensen A/S

Rosenkaeret 25-29

DK-2860 Søborg

Denmark

Tel: +45 39 53 03 11

Contact person

Mikael Jensen

E-mail

miljo@bj.dk

Revision

8/29/2022

SDS Version

1.0

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)

General

Prevention

Avoid release to the environment. (P273)

Response



Storage

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

No special.

Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-on, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

This paint contains a biocidal product for the preservation of the dry film.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

VOC

VOC content: 79 g/L

MAXIMUM VOC CONTENT (Phase II, category A/d (WB): 130 g/L)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Titandioxid	CAS No.: 13463-67-7	15-25%		
	EC No.: 236-675-5			
	REACH: 01-2119489379-17			
	Index No.:			
propane-1,2-diol	CAS No.: 57-55-6	5-10%		
	EC No.: 200-338-0			
	REACH: 01-211945809-23			
	Index No.:			
2-butoxyethanol	CAS No.: 111-76-2	<1%	Acute Tox. 4, H302	[1]
	EC No.: 203-905-0		Skin Irrit. 2, H315 Eye Irrit. 2, H319	
	REACH: 01-2119475108-36		Acute Tox. 4, H332	
	Index No.: 603-014-00-0			
3-iodo-2-	CAS No.:	<1%	Acute Tox. 4, H302	
propynylbutylcarbamat (indkapslet)	EC No.:		Acute Tox. 3, H331 STOT RE 1, H372	
	REACH:			
	Index No.:			
3-iodo-2-propynyl	CAS No.: 55406-53-6	<0.05%	Acute Tox. 4, H302	

754-xxx Cover It Page 2 of 28



butylcarbamate 3- iodoprop-2-yn-1-yl butylcarbamate	EC No.: 259-627-5 REACH: Index No.: 616-212-00-7		Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)
1,2-benzisothiazol-3(2H)- on	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.036 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411
terbutryn	CAS No.: 886-50-0 EC No.: 212-950-5 REACH: Index No.:	<0.05%	Acute Tox. 4, H302 Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
reaction mass of 5-chloro- 2-methyl-2H-isothiazol-3- one and 2-methyl-2H- isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: REACH: Index No.: 613-167-00-5	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
2-methyl-2H-isothiazol-3- one	CAS No.: 2682-20-4 EC No.: 220-239-6 REACH: Index No.:	<0.0015%	Flam. Liq. 1, H224 Acute Tox. 3, H301 Skin Corr. 1B, H314 Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 Acute Tox. 1, H330 (ATE: 0.50 mg/l) STOT SE 3, H335 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.



Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eve contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction in already sensitized persons.

4.3. Indication of any immediate medical attention and special treatment needed

No special.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling



It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titandioxid

Long term exposure limit (8 hours) (mg/m³): 6 (som Ti)

Annotations:

K = Dusts that contain the substance on a respirable form are considered to be carcinogenic.

1-butoxypropan-2-ol

Long term exposure limit (8 hours) (ppm): 100

2-butoxyethanol

Long term exposure limit (8 hours) (mg/m³): 98

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (mg/m³): 246

Short term exposure limit (15 minutes) (ppm): 50

Annotations:

E = Substance has an EC limit.

H = The substance can be absorbed through the skin.

ammoniak, vandfri

Long term exposure limit (8 hours) (mg/m³): 14

Long term exposure limit (8 hours) (ppm): 20

Annotations:

E = Substance has an EC limit.

Statutory order 1054 on exposure limits for substances and mixtures (28/06/2022)

Titandioxid is included in the national list of substances suspected of causing cancer

BEK nr 1795 af 18/12/2015 om foranstaltninger til forebyggelse af kræftrisikoen ved arbejde med stoffer og materialer.

DNEL

1-butoxypropan-2-ol

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	22 mg/kg/day
Long term – Systemic effects - Workers	Dermal	52 mg/kg/day
Long term – Systemic effects - General population	Inhalation	43 mg/m³



Long term – Systemic effects - Workers	Inhalation	147 mg/m³
Long term – Systemic effects - General population	Oral	12,5 mg/kg/day
2-butoxyethanol		
Duration	Route of exposure	DNEL
Long term – Local effects - General population	Dermal	147 mg/m³
Long term – Systemic effects - General population	Dermal	75 mg/kg
Long term – Systemic effects - Workers	Dermal	125 mg/kg/d
Short term – Systemic effects - General population	Dermal	89 mg/kg/d
Short term – Systemic effects - Workers	Dermal	89 mg/kg
Long term – Systemic effects - General population	Inhalation	59 mg/m³
Long term – Systemic effects - Workers	Inhalation	98 mg/kg
Short term – Local effects - Workers	Inhalation	246 mg/m3
Short term – Systemic effects - General population	Inhalation	426 mg/m³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m³
Long term – Systemic effects - General population	Oral	6,3 mg/kg/d
Short term – Systemic effects - General population	Oral	26,7 mg/kg/d
propane-1,2-diol		
Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	213 mg/kg/day
Long term – Local effects - General population	Inhalation	10 mg/m3
Long term – Local effects - Workers	Inhalation	10 mg/m3
Long term – Systemic effects - General population	Inhalation	50 mg/m3
Long term – Systemic effects - Workers	Inhalation	168 mg/m3
Long term – Systemic effects - General population	Oral	85 mg/kg/day
Titandioxid		
Duration	Route of exposure	DNEL
Long term – Local effects - Workers	Inhalation	10 mg/m3
Long term – Systemic effects - General population	Oral	700 mg/kg bw/day
	Oral	
Soil	Single	
Water	Single	0,005 mg/l
vvalci	Siligie	0,0005 mg/l

754-xxx Cover It Page 6 of 28

1-butoxypropan-2-ol



Route of exposure	Duration of Exposure	PNEC
Freshwater	-	0,525 mg/l
Intermittent release	-	5,25 mg/l
Marine water	-	0,0525 mg/l
Sewage treatment plant	-	10 mg/l
2-butoxyethanol		
Route of exposure	Duration of Exposure	PNEC
Activated Sludge Plant	-	463 mg/l
Freshwater	-	8,8 mg/l
Freshwater sediment	-	8,14 mg/kg
Marine water	-	0,88 mg/l
Marine water sediment	-	3,46 mg/kg
Soil	-	2,8 mg/kg
propane-1,2-diol		
Route of exposure	Duration of Exposure	PNEC
Freshwater	-	260 mg/l
Freshwater sediment	-	572 mg/kg
Intermittent release	-	183 mg/L
Marine water	-	26 mg/L
Marine water sediment	-	57,2 mg/kg
Sewage treatment plant	-	20000 mg/L
Soil	-	50 mg/kg
Fitandioxid		
Route of exposure	Duration of Exposure	PNEC
Freshwater	-	0,184 mg/l
Freshwater sediment	-	1000 mg/l
Intermittent release	-	0,193 mg/l
Marine water	-	0,0184 mg/l
Marine water Marine water sediment	-	0,0184 mg/l 100 mg/Kg
	-	<u>-</u>

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

754-xxx Cover It Page 7 of 28



There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Only CE-marked personal protection equipment should be used.

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Туре	Class	Colour	Standards	
Non industrial spraying	Combination filter A2P3	Class 2/3	Brown/White	EN14387	

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	R

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Latex	0.4	-	EN374-2, EN388	

Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Various colours

Odour / Odour threshold

Faint

На

8-9



Density (g/cm³)

1.23

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

100

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

Ignition (°C)

Testing not relevant or not possible due to the nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (q/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

VOC (g/L)

79

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special.

10.4. Conditions to avoid

No special.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.



SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/substance

Titandioxid

Test method

Species Rat
Route of exposure Oral
Test LD50

Result >5000 mg/Kg ·

Other information

Product/substance

Titandioxid

Test method

Species Rat
Route of exposure Inhalation
Test LC50

Result $> 3,43 - 5,09 \text{ mg/l} \cdot$

Other information

Product/substance

propane-1,2-diol

Test method

Species Rat
Route of exposure Oral
Test LD50

Result 22000 mg/kg ·

Other information

Product/substance

propane-1,2-diol

Test method

Species Rabbit
Route of exposure Dermal
Test LD50
Result 2000 mg/kg ·

Other information

Product/substance

propane-1,2-diol

Test method

Species Rabbit
Route of exposure Inhalation
Test LC50
Result 317 mg/l·

Other information

Product/substance

1-butoxypropan-2-ol

Test method

Species Rat
Route of exposure Oral
Test LD50
Result 3300 mg/kg ·

3 3



	rmation	

Product/substance

1-butoxypropan-2-ol

Test method

Species Rat
Route of exposure Dermal
Test LD50
Result 2000 mg/kg ·

Other information

Product/substance

2-butoxyethanol

Test method

Species Rabbit
Route of exposure Dermal
Test LD50
Result 210 mg/kg ·

Other information

Product/substance

2-butoxyethanol

Test method

Species Rabbit
Route of exposure Oral
Test LD50
Result 300 mg/kg ·

Other information

Product/substance

2-butoxyethanol

Test method

Species Rat
Route of exposure Inhalation
Test LC50

Result

2,21 mg/l/4h ·

Other information

Product/substance

2-butoxyethanol

Test method

Species Rat
Route of exposure Oral
Test LD50

Result $> 200 - < 2000 \text{ mg/kg} \cdot$

Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method

Species Rat
Route of exposure Oral
Test LD50

Result

300-500 mg/kg ·

Other information

Product/substance

Test method

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate



Species

Rat

Route of exposure

Inhalation LC50

Test Result

6,89 mg/l (4 h) ·

Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method

Rabbit Species Route of exposure Dermal LD50 Test

Result > 2000 mg/kg ·

Other information

Product/substance

Test method

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species Route of exposure

Oral LC50 Test

Result 670 mg/m³ (4 h, dust) ·

Rat

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Rat Species Route of exposure Oral Test LD50

Result 1193 mg/Kg ·

Other information

Product/substance Test method

1,2-benzisothiazol-3(2H)-on

Species Rat Route of exposure Dermal LD50 Test 4115 mg/Kg · Result

Other information

Product/substance Test method

terbutryn

Species Rat Route of exposure Oral Test LD50

2045 mg/Kg · Result

Other information

Product/substance

terbutryn

Test method

Species Mouse Oral Route of exposure LD50 Test

Result 3884 mg/Kg ·

754-xxx Cover It Page 12 of 28



Other information

Product/substance

terbutryn

> 10200 mg/Kg ·

Test method

Species Rabbit
Route of exposure Dermal
Test LD50

Result

Other information

Product/substance

terbutryn

Test method

Species Rat

Route of exposure Inhalation Test LC50

Result >5,34 mg/l (4 h) ·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Rat
Route of exposure Oral
Test LD50

Result 49,6 - 75 mg/Kg ·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Rat

Route of exposure Inhalation
Test LC50

Result 0,33 mg/l, 4 h, aerosol ·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Rabbit
Route of exposure Dermal
Test LD50

Result 200 - 1000 mg/Kg ·

Other information

Product/substance

2-methyl-2H-isothiazol-3-one

Test method

Species Rat
Route of exposure Oral
Test LD50
Result 183 mg/Kg ·

Other information

Product/substance 2-methyl-2H-isothiazol-3-one

Test method



Species Rat
Route of exposure Inhalation
Test LC50
Result 0,11 mg/l·

Other information

Product/substance

2-methyl-2H-isothiazol-3-one

Test method

Species Rabbit
Route of exposure Dermal
Test LD50
Result 242 mg/Kg ·

Other information

Skin corrosion/irritation

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method OECD 404 Species Rabbit

Duration

Result Adverse effect observed (Irritating)

Other information

Serious eye damage/irritation

Product/substance 1,2-benzisothiazol-3(2H)-on Test method no guideline followed

Species Duration

Result Adverse effect observed (Causes serious eye damage)

Other information

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method

Species Human

Result Adverse effect observed (sensitising)
Other information Can course allergic reaction at skin contact

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Human

Result Adverse effect observed (sensitising)
Other information Can course allergic reaction at skin contact

Product/substance

2-methyl-2H-isothiazol-3-one

Test method

Species Human

Result Adverse effect observed (sensitising)
Other information Can course allergic reaction at skin contact

754-xxx Cover It Page 14 of 28



Germ cell mutagenicity

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species

Conclusion No adverse effect observed

Other information

Carcinogenicity

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species

Route of exposure Target organ Duration

Test Result

Conclusion

No adverse effect observed

Other information

Reproductive toxicity

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species Duration

Test Result

Conclusion No adverse effect observed

Other information

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

No special.

Endocrine disrupting properties

No special.

Other information

Titandioxid has been classified by IARC as a group 2B carcinogen.

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance

Titandioxid

Test method

Species Fish

Compartment

754-xxx Cover It Page 15 of 28



Duration 96 hours Test LC50 >1000 mg/l · Result

Titandioxid

Titandioxid

propane-1,2-diol

propane-1,2-diol

propane-1,2-diol

Daphnia

Algae

Fish

Daphnia

Other information

Product/substance

Test method

Species

Compartment

48 hours Duration EC50 Test Result >1000 mg/l ·

Other information

Product/substance

Test method

Species

Compartment

72 hours Duration Test EC50 61 mg/l · Result

Other information

Product/substance

Test method

Species

Compartment

Duration 96 hours Test LC50

> 40613 mg/l · Result

Other information

Product/substance

Test method

Species

Compartment

Duration 48 hours EC50 Test 18800 mg/l · Result

Other information

Product/substance Test method

Algae

Species Compartment

Duration

96 hours Test EC50 19000 mg/l · Result

Other information

Product/substance

Test method

propane-1,2-diol

754-xxx Cover It Page 16 of 28



Species

Algae

Compartment

Duration 72 hours
Test EC50
Result 24200 mg/l·

Other information

Product/substance

1-butoxypropan-2-ol

Test method

Species Daphnia

Compartment

 $\begin{array}{ll} \text{Duration} & 48 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & > 1000 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance

1-butoxypropan-2-ol

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 96 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & > 1000 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance
Test method

1-butoxypropan-2-ol

Algae

Species

Species

Compartment

Duration 96 hours
Test NOEC
Result 560 mg/l ·

Other information

Product/substance

2-butoxyethanol

Test method

Species Fish

Compartment

Duration 96 hours Test LC50

Result 820 - 1490 mg/l ·

Other information

Product/substance

2-butoxyethanol

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50

Result 835 - 1550 mg/l ·

Other information

754-xxx Cover It Page 17 of 28



Product/substance

2-butoxyethanol

Test method

Species Algae

Compartment

Duration 72 hours
Test IC50
Result 1840 mg/l·

Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method

Species Fish

Compartment

Duration 96 hours Test LC50 Result 0,049 mg/l \cdot

Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method Species

Species

Compartment

Duration 48 hours
Test EC50
Result 0,160 mg/l·

Other information

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Daphnia

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{IC50} \\ \text{Result} & 0,022 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method Species

pecies Daphnia

Compartment

 $\begin{array}{ll} \text{Duration} & 21 \text{ days} \\ \text{Test} & \text{NOEC} \\ \text{Result} & 1,3 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method

Species Fish

Compartment

 $\begin{array}{ll} \text{Duration} & 21 \text{ days} \\ \text{Test} & \text{NOEC} \\ \text{Result} & 0,01 \text{ mg/l} \cdot \end{array}$

754-xxx Cover It Page 18 of 28



Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method

Species Daphnia

Compartment

Duration 21 days
Test EC50
Result 0,05 mg/l·

Other information

Product/substance

Test method

Species Fish

Compartment

Duration 35 d.
Test NOEC
Result 0,0084 mg/l·

Other information

Product/substance

Test method

Species Algae

Compartment

Duration 72 hours
Test NOEC
Result 0,0046 mg/l·

Other information

Product/substance

ostance 1,2-benzisothiazol-3(2H)-on

Fish

Test method

Species

Compartment

 $\begin{array}{ll} \text{Duration} & 96 \text{ hours} \\ \text{Test} & \text{LC50} \\ \text{Result} & 1,3 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance Test method 1,2-benzisothiazol-3(2H)-on

restilletilou

Species Daphnia

Compartment

Duration 96 hours
Test EC50
Result 1,5 mg/l·

Other information

Product/substance

Test method Species 1,2-benzisothiazol-3(2H)-on

Algae

Compartment

Duration 48 hours

754-xxx Cover It Page 19 of 28



Test EC50

Result 0,055 mg/l⋅

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Daphnia

Compartment

 $\begin{array}{lll} \text{Duration} & \text{48 hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & \text{2,94 mg/l} \cdot \end{array}$

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Species Algae

Compartment

 $\begin{array}{lll} \text{Duration} & 24 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 0,11 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method

Species Fish

Compartment

Duration No data available.

Test NOEC Result 0,21 mg/l·

Other information

Product/substance 1,2-benzisothiazol-3(2H)-on

Test method

Species Daphnia

Compartment

Duration 21 days
Test NOEC
Result 1,2 mg/l·

Other information

Product/substance terbutryn

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 7 \text{ days} \\ \text{Test} & \text{EC50} \\ \text{Result} & 0,013 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance terbutryn

Test method

Species Daphnia

754-xxx Cover It Page 20 of 28



Compartment

Duration 48 hours EC50 Test Result 2,66 mg/l ·

Other information

Product/substance

terbutryn

Test method

Fish Species

Compartment

96 hours Duration Test LC50 0,067 mg/l· Result

Other information

Product/substance

terbutryn

Test method

Daphnia **Species**

Compartment

Duration 21 days Test NOEC Result 1,3 mg/l ·

Other information

Product/substance

terbutryn

Test method

Fish **Species**

Compartment

35 d. Duration NOEC Test 0,84 mg/l · Result

Other information

Product/substance terbutryn

Test method

Species Fish

Compartment

21 days Duration NOEC Test 0,01 mg/l · Result

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Fish

Compartment

Duration 96 hours LC50 Test Result 0,19 mg/l ·

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

754-xxx Cover It Page 21 of 28



Test method

Species Daphnia

Compartment

 $\begin{array}{ll} \text{Duration} & \text{48 hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & \text{0,10 mg/l} \cdot \end{array}$

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 0,048 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species

Compartment

Algae

Duration 96 hours
Test NOEC
Result 0,032 mg/l·

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Daphnia

Compartment

 $\begin{array}{ll} \text{Duration} & 21 \text{ days} \\ \text{Test} & \text{EC50} \\ \text{Result} & > 1 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Fish

Compartment

 $\begin{array}{lll} \text{Duration} & 96 \text{ hours} \\ \text{Test} & \text{LC50} \\ \text{Result} & 0,58 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Fish

Compartment

Duration 34 d. Test NOEC Result $0.5 \text{ mg/l} \cdot$

Other information

754-xxx Cover It Page 22 of 28



Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Algae

Compartment

Duration 48 hours
Test NOEC
Result 0,00064 mg/l·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Daphnia

Compartment

Duration 21 days
Test NOEC
Result 0,004 mg/l·

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method Species

Compartment

Duration 28 days
Test NOEC
Result 0,098 mg/l·

Fish

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Species Algae

Compartment

 $\begin{array}{lll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{NOEC} \\ \text{Result} & 0,0012 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance

2-methyl-2H-isothiazol-3-one

Test method

Species Fish

Compartment

 $\begin{array}{ll} \text{Duration} & 96 \text{ hours} \\ \text{Test} & \text{LC50} \\ \text{Result} & 4,77 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance 2-methyl-2H-isothiazol-3-one

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result 0,18 mg/l·

754-xxx Cover It Page 23 of 28



Other information

Product/substance

2-methyl-2H-isothiazol-3-one

Test method

Species Algae

Compartment

Duration

Test

Result

72 hours EC50 0,16 mg/l ·

Other information

12.2. Persistence and degradability

Product/substance

propane-1,2-diol

Biodegradable

Test method

Yes

Yes

Result BOD5/COD > 0,5

Product/substance Biodegradable

1-butoxypropan-2-ol

Test method Result

2-butoxyethanol

Biodegradable

Product/substance

Yes

Test method

Result

OECD 301 C 88% efter 28 dage

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Biodegradable Test method Result

Product/substance

1,2-benzisothiazol-3(2H)-on

Biodegradable Test method

Result

Yes

Product/substance Biodegradable

terbutryn No

Test method

Result

12.3. Bioaccumulative potential

Product/substance

propane-1,2-diol

Test method

LogPow BCF

Potential No

bioaccumulation

-1,4000 0,09

Other information

754-xxx Cover It Page 24 of 28



Product/substance

1-butoxypropan-2-ol

Test method

Potential

bioaccumulation

LogPow 1,1500

BCF No data available.

No

Other information

Product/substance

2-butoxyethanol

Test method

Potential No

bioaccumulation

LogPow 0,8000 BCF 2,5

Other information

Product/substance

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Test method

Potential No

bioaccumulation

LogPow 2,8100

BCF No data available.

Other information

Product/substance

1,2-benzisothiazol-3(2H)-on

Test method

Potential

bioaccumulation

LogPow 1,3000

BCF No data available.

Other information

Product/substance

terbutryn

No

Test method

Potential No data available.

bioaccumulation

LogPow 3,6900

BCF No data available.

Other information

Product/substance

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method

Potential No

bioaccumulation

LogPow 0,4000 BCF 3,6

Other information

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.



12.6. Endocrine disrupting properties

No special.

12.7. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

ammoniak, vandfri

Additional information

Code number (1993): 00-1

Sources

Executive Order no. 372 of 25 April 2016 on control of the risk of major accidents with dangerous substances. Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products.

Executive Order no. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car repair painting.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

^{**} Environmental hazards



Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H224, Extremely flammable liquid and vapour.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H331, Toxic if inhaled.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H372, Causes damage to organs through prolonged or repeated exposure.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic



PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The safety data sheet is validated by

XXX

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en