

## Product information

Beck & Jorgensen A/S

### Product Description

Semi-gloss window paint with its Special binder composition provides good adhesion and weather-resistant surface. The product fade very little and has a minimal tendency to block..

Contains materials, that protect the film against surface mold.

### Directions for use

It is recommended that the surface is firm, clean and dry (max. wood moisture 20%) and no chalking. Any resinous secretions should be removed with appropriate thinner. Do not carry out the application at temperatures below +10 ° C.

Is it necessary that the subject must be impregnated use an appropriate Wood preserver.

Apply two to three coats for durable, attractive finish.

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Remarks

Moisture content of the windows must be 12 + - 3% in freestanding wood and ventilated cladding max. 18%.

## Technical data

<b>Binder:</b>	Combination of acrylic and alkyd
<b>Type:</b>	
<b>Gloss:</b>	Approx. 30, semigloss
<b>Vol. dry:</b>	Approx. 37%
<b>Colours:</b>	White, RAL 9010. Can be tinted
<b>Drying:</b>	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
<b>Application:</b>	+10 °C to + 25° C. RH: 40-80%
<b>Thinning:</b>	Water. Normally not to be diluted
<b>Coverage:</b>	Rough saw timber: 2-5 m <sup>2</sup> /Liter Planed timber: 8-10 m <sup>2</sup> /Liter

### Tools:

**Mal-Code:** 00-1 (1993)

