

756 Roof Paint



Product information

Beck & Jørgensen A/S

Product Description

Semi mat acrylic paint for maintenance of coloured cement fiber roof.

Contains materials, that protect the film against surface mold.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Contaminations has to be treated with detergent.

Paint the roof 1-2 times with Roof paint 756.

Priming of porous and water absorbing surfaces with Microprimer 716 or semilar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

Cleaning of asbestos has to be done accordingly to legislation.

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
----------	--------	--------------	----------	--------

Technical data

Binder: Acrylic

Type: Acrylic paint

Gloss: Approx. 30, semigloss

Vol. dry:

Colours:

Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.

Application: +10 °C to + 25° C. RH: 40-80%

Thinning:

Coverage: 5-10 m²/ltr. Depending on the absorption

Tools: Brush, Roller or Spraying

Mal-Code: 00-1 (1993)

