

# 757 Emulsion paint Water Based



## Product information

Beck & Jørgensen A/S

### Product Description

Dull mat masonry paint for previously painted surfaces, with good adherents to well cleaned chalky surfaces. The combination between alkyd and acrylic secures penetration and adheres to the surface. The finish is a dull mat and water repellent surface, and the product contains encapsulated fungicides that give a long-lasting protection against surface mold. The Sd value for the product is 0,3m Class V2 /EN 1062-1

### Directions for use

The substrate must be clean, dry, and sound / stable and free from all substances that may prevent good adhesion. Crack and holes shall be repaired with filler. Remove surface fouling with appropriate cleaner. Priming of porous and water absorbing surfaces with Mikrodispers 716, Mikrotix 717 or paint thinned 10-15% water. Not to be used on alkaline surfaces.

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.  
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.  
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.  
Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

### Technical data

**Binder:** Oil emulsion  
**Type:** Alkyd /acrylic emulsion water based  
**Gloss:** Approx. 3 Flat matt  
**Vol. dry:** Apros 45%  
**Colours:** White and B&J tinting system  
**Drying:** 2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF  
**Application:** +10 °C to + 25° C. RH: 40-80%  
**Thinning:** Water  
**Coverage:** Rough saw timber: 2-5 m<sup>2</sup>/Liter  
Planed timber: 8-10 m<sup>2</sup>/Liter

**Tools:** Brush, roller or airless  
**Mal-Code:**

