

### Product Description

Good quality wall paint with fine coverage.  
Usable for walls of concrete, plaster and wallcoverings  
The product is suitable for domestic houses and apartments,

### Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.  
Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.  
Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

### Cleaning instructions

Clean with water immediately after use. Once a week clean the equipment using an appropriate cleaning agent.

### Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.  
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.  
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.  
Further information and MSDS on [www.bj.dk](http://www.bj.dk)

### Remarks

This product has been qualified for the EU Eco-label by reducing the water and air pollution as well as the quantity of waste.  
Further information on why this product was assigned with EU Eco-label can be found on [www.ecolabel.eu](http://www.ecolabel.eu)

### Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

### Technical data

**Binder:** Polyvinylacetate  
**Type:** Wall Paint / ceiling paint  
**Gloss:** App. 5, matt  
**Vol. dry:**  
**Colours:** White, Off white, NCS-S 0500 and B&J tinting system  
**Drying:** App. 2-4 hours at 20° C. RH.: 65%. Recoatable after app. 8 hours.  
**Application:** +10 °C to + 25° C. RH: 40-80%  
**Thinning:** Water  
**Coverage:** 8-10 m<sup>2</sup>/ltr  
**Tools:** Brush, roller or airless  
**Mal-Code:** 00-1 (1993)

