



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

766-xxx Acryl 6 vægmaling

Product no.

766001

REACH registration number

Not applicable

Unique formula identifier (UFI)

-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Beck & Jorgensen A/S
Rosenkaeret 25-29
DK-2860 Soeborg, Denmark
Phone: +45 39 53 03 11
www.bj.dk

Contact person

Mikael Jensen

E-mail

miljo@bj.dk

SDS date

2019-06-18

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

2.2. Label elements

Hazard pictogram(s)

Not applicable

Signal word

-

Hazard statement(s)

Not applicable

Precautionary statements

General

-

Prevention

Avoid breathing vapours/spray. (P261).

[In case of inadequate ventilation] wear respiratory protection. (P284).

Response

-

According to EC-Regulation 2015/830

Storage -
Disposal -

Identity of the substances primarily responsible for the major health hazards

Not applicable

2.3. Other hazards

Not applicable

Additional labelling

Contains 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]. May produce an allergic reaction. (EUH208).

Safety data sheet available on request. (EUH210)

Additional warnings

Not applicable

VOC (volatile organic compound)

VOC-Max: 25 g/l, MAXIMUM VOC CONTENT (A/a (WB)): 30 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	Quartz (SiO ₂)
IDENTIFICATION NOS.:	CAS-no: 14808-60-7 EC-no: 238-878-4
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	STOT RE 2 H373
NAME:	propane-1,2-diol
IDENTIFICATION NOS.:	CAS-no: 57-55-6 EC-no: 200-338-0 REACH-no: 01-211945809-23
CONTENT:	1 - <2.5%
CLP CLASSIFICATION:	NA
NAME:	2-phenoxyethanol
IDENTIFICATION NOS.:	CAS-no: 122-99-6 EC-no: 204-589-7 Index-no: 603-098-00-9
CONTENT:	0.25 - <1%
CLP CLASSIFICATION:	Acute Tox. 4, Eye Irrit. 2 H302, H319
NAME:	2-n-butyl-benzo[d]isothiazol-3-one
IDENTIFICATION NOS.:	CAS-no: 4299-07-4 EC-no: 420-590-7 Index-no: 606-079-00-3
CONTENT:	<0.01%
CLP CLASSIFICATION:	Skin Corr. 1B, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1 H314, H317, H400, H410 (M-acute = 1) (M-chronic = 1)
NAME:	2-methyl-2H-isothiazol-3-one
IDENTIFICATION NOS.:	CAS-no: 2682-20-4 EC-no: 220-239-6
CONTENT:	<0.01%
CLP CLASSIFICATION:	Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1A, Eye Dam. 1, Acute Tox. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 2 H301, H314, H317, H318, H330, H335, H400, H411 (M-acute = 1)
NAME:	5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
IDENTIFICATION NOS.:	CAS-no: 55965-84-9 Index-no: 613-167-00-5
CONTENT:	<0.0015%
CLP CLASSIFICATION:	Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1A, Eye Dam. 1, Acute Tox. 3, Aquatic Acute 1, Aquatic Chronic 1 H301, H311, H314, H317, H318, H331, H400, H410 (M-acute = 1) (M-chronic = 1)

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

A_TEmix(inhale, vapour) > 20
A_TEmix(dermal) > 2000
A_TEmix(oral) > 2000

SECTION 4: First aid measures



According to EC-Regulation 2015/830

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction to predisposed persons.

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Some metal oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

propane-1,2-diol

Long-term exposure limit (8-hour TWA reference period): - ppm | - mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

DNEL (propane-1,2-diol): 168 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (propane-1,2-diol): 10 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (propane-1,2-diol): 50 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propane-1,2-diol): 10 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (propane-1,2-diol): 85 mg/kg/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propane-1,2-diol): 213 mg/kg/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-phenoxyethanol): 8,07 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-phenoxyethanol): 34,72 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-phenoxyethanol): 2,5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (2-phenoxyethanol): 20,83 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Local effects - General population

DNEL (2-phenoxyethanol): 17,43 mg/kg

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

PNEC (propane-1,2-diol): 260 mg/l

Exposure: Freshwater

PNEC (propane-1,2-diol): 57,2 mg/kg

Exposure: Marine water sediment

According to EC-Regulation 2015/830

Remarks: ECHA

PNEC (propane-1,2-diol): 572 mg/kg
Exposure: Freshwater sediment
Remarks: ECHA

PNEC (propane-1,2-diol): 20000 mg/L
Exposure: Sewage Treatment Plant
Remarks: ECHA

PNEC (propane-1,2-diol): 183 mg/L
Exposure: Intermittent release
Remarks: ECHA

PNEC (propane-1,2-diol): 26 mg/L
Exposure: Marine water
Remarks: ECHA

PNEC (propane-1,2-diol): 50 mg/kg
Exposure: Soil
Remarks: ECHA

PNEC (2-phenoxyethanol): 0,943 mg/l
Exposure: Freshwater

PNEC (2-phenoxyethanol): 0,0943 mg/l
Exposure: Marine water

PNEC (2-phenoxyethanol): 7,23 mg/kg
Exposure: Freshwater sediment

PNEC (2-phenoxyethanol): 0,723 mg/kg
Exposure: Marine water sediment

PNEC (2-phenoxyethanol): 1,26 mg/kg
Exposure: Soil

PNEC (2-phenoxyethanol): 3,44 mg/l
Exposure: Intermittent release

PNEC (2-phenoxyethanol): 24,8 mg/l
Exposure: Sewage Treatment Plant

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, eating and drinking are not allowed in the work premises

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



According to EC-Regulation 2015/830

Generally

Use only CE marked protective equipment.

Respiratory Equipment

If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an air-supplied breathing apparatus depending on the specific work situation and how long you will be using the product.

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester. Chemical resistant suit with helmet/hood (Type 4, 5, 6 Category III) is recommended for spray applications.

Hand protection

Nitrile rubber

Discard immediately after use

Eye protection

Wear face shield alternatively safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Various colours
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	8-9
Viscosity (40°C)	No data available.
Density (g/cm ³)	1,13

Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

Solubility

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: 200 - 1000 mg/Kg

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 49,6 - 75 mg/Kg

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 0,33 mg/l, 4 h, aerosol

Substance: 2-methyl-2H-isothiazol-3-one
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: 242 mg/Kg

Substance: 2-methyl-2H-isothiazol-3-one
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 183 mg/Kg

Substance: 2-methyl-2H-isothiazol-3-one
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 0,11 mg/l

Substance: 2-phenoxyethanol
Species: Rat
Test: LD50
Route of exposure: Dermal
Result: > 2000 mg/kg

Substance: 2-phenoxyethanol
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 1850 mg/kg

Substance: propane-1,2-diol
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: 2000 mg/kg

Substance: propane-1,2-diol
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 22000 mg/kg

Substance: propane-1,2-diol
Species: Rabbit
Test: LC50
Route of exposure: Inhalation
Result: 317 mg/l

Skin corrosion/irritation

No data available.



According to EC-Regulation 2015/830

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

Data on substance: 2-methyl-2H-isothiazol-3-one

Data on substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Organism: Human

Result: Can course allergic reaction at skin contact

Data on substance: 2-methyl-2H-isothiazol-3-one

Organism: Human

Result: Can course allergic reaction at skin contact This product contains substances that may trigger an allergic reaction to predisposed persons.

Germ cell mutagenicity

Data on substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Result: No effect in experiments on animals

No adverse effect observed.

Data on substance: 2-methyl-2H-isothiazol-3-one

Carcinogenicity

Data on substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Result: No effect in experiments on animals

No adverse effect observed.

Reproductive toxicity

Data on substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Result: No effect in experiments on animals

No adverse effect observed.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Nothing special

SECTION 12: Ecological information

12.1. Toxicity

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Species: Fish

Test: LC50

Duration: 96 h

Result: 0,19 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Species: Daphnia

Test: EC50

Duration: 48 h

Result: 0,16 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Species: Algae

Test: EC50

Duration: 72 h

Result: 0,379 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]

Species: Algae

Test: EC50

According to EC-Regulation 2015/830

Duration: 96 h
Result: 0,166 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Algae
Test: NOEC
Duration: 96 h
Result: 0,032 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Daphnia
Test: EC50
Duration: 21 days
Result: > 1 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Daphnia
Test: EC50
Duration: 48 h
Result: 1,02 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Fish
Test: LC50
Duration: 96 h
Result: 0,58 mg/l

Substance: 5-chlor-2-methyl-2H-isothiazol-3-on [EU-No.247-500-7], mix (3:1) 2-methyl-2H-isothiazol-3-on [EU-No.220-239-6]
Species: Fish
Test: NOEC
Duration: 34 days
Result: 0,5 mg/l

Substance: 2-methyl-2H-isothiazol-3-one
Species: Fish
Test: LC50
Duration: 96 h
Result: 4,77 mg/l

Substance: 2-methyl-2H-isothiazol-3-one
Species: Daphnia
Test: EC50
Duration: 48 h
Result: 0,18 mg/l

Substance: 2-methyl-2H-isothiazol-3-one
Species: Algae
Test: EC50
Duration: 72 h
Result: 0,16 mg/l

Substance: 2-n-butyl-benzo[d]isothiazol-3-one
Species: Fish
Test: LC50
Duration: 96 h
Result: 0,15 mg/l

Substance: 2-n-butyl-benzo[d]isothiazol-3-one
Species: Daphnia
Test: EC50
Duration: 48 h
Result: 0,093 mg/l

Substance: 2-n-butyl-benzo[d]isothiazol-3-one
Species: Algae
Test: ErC50
Duration: 72 h
Result: 0,45 mg/l

Substance: propane-1,2-diol
Species: Fish
Test: LC50
Duration: 96 h
Result: > 40613 mg/l

According to EC-Regulation 2015/830

Substance: propane-1,2-diol
Species: Daphnia
Test: EC50
Duration: 48 h
Result: 18800 mg/l

Substance: propane-1,2-diol
Species: Algae
Test: EC50
Duration: 96 h
Result: 19000 mg/l

Substance: propane-1,2-diol
Species: Algae
Test: EC50
Duration: 72 h
Result: 24200 mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
propane-1,2-diol	Yes	No data available	BOD5/COD > 0,5

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
5-chlor-2-methyl-2H-isothiazol...	No	0,4	3,6
propane-1,2-diol	No	-1,4	0,09

12.4. Mobility in soil

5-chlor-2-methyl-2H-isothiazol...: Log Koc= 0,39516, Calculated from LogPow (High mobility potential.).
propane-1,2-diol: Log Koc= -1,03026, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which due to poor biodegradability, may cause adverse long-term effects to the aquatic environment,

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Waste

EWC code

08 01 12

waste paint and varnish other than those mentioned in 08 01 11

Specific labelling

Not applicable

Contaminated packing

No specific requirements.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

Notes

-

Tunnel restriction code

-

IMDG

UN-no.

-



According to EC-Regulation 2015/830

Proper Shipping Name	-
Class	-
PG*	-
Em S	-
MP**	-
Hazardous constituent	-
IATA/ICAO	
UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

Not applicable

Seveso

-

Sources

Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H301 - Toxic if swallowed.

H302 - Harmful if swallowed.

H311 - Toxic in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H319 - Causes serious eye irritation.



According to EC-Regulation 2015/830

- H330 - Fatal if inhaled.
- H331 - Toxic if inhaled.
- H335 - May cause respiratory irritation.
- H373 - May cause damage to organs through prolonged or repeated exposures.
- H400 - Very toxic to aquatic life.
- H410 - Very toxic to aquatic life with long lasting effects.
- H411 - Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

admin

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-

ALPHAOMEGA. Licens nr.:3624221651, 6.5.0.18
www.chymeia.com