

766 Super Finish 6, Acryl 6



Product information

Beck & Jørgensen A/S

Product Description

High quality acrylic wall paint with excellent coverage and low odour.

The product is very resistant to burnish and performs perfect in domestic houses, for living rooms and kitchens as well as in offices, kindergartens and shops.

The resistance to burnish combined with the wet scrub Class 1, according to EN 13300, makes it a perfect choice, where the best result is wanted.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Acrylic

Type:

Gloss: App. 6, matt

Vol. dry:

Colours: White, Off white, NCS-S 0500 and B&J tinting system

Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water

Coverage: 8-10 m²/ltr

Tools: Brush, roller or airless

Mal-Code:

