

Product Description

Good quality wall paint with fine coverage.
Usable for walls of concrete, plaster, and wallcoverings
For domestic houses and appartments, where extra gloss is wanted.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.
Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.
Priming of porous and water absorbing surfaces with Microprimer 716 or semilar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.
Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.
Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.
Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Polyvinylacetate
Type: Wall paint
Gloss: Approx. 10, semi matt
Vol. dry:
Colours: White, Off white, NCS-S 0500 and B&J tinting system in light shades
Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours.
Application: +10 °C to + 25° C. RH: 40-80%
Thinning: Water
Coverage: 8-10 m²/ltr
Tools: Brush, roller or airless
Mal-Code: 00-1 (1993)

