

SAFETY DATA SHEET

771 Strygepuds Grov

SECTION 1: Identification of the substance/mixture and of the company/undertaking

```
1.1. Product identifier
   ▼ Trade name
     771 Strygepuds Grov
  Product no.
     771111
1.2. Relevant identified uses of the substance or mixture and uses advised against
  Relevant identified uses of the substance or mixture
     Strygepuds til facader
   ▼ Uses advised against
     None known.
1.3. Details of the supplier of the safety data sheet
  Company and address
     Beck & Jørgensen A/S
     Rosenkaeret 25-29
     DK-2860 Søborg
     Denmark
     Tel: +45 39 53 03 11
  Contact person
     Mikael Jensen
  E-mail
     miljo@bj.dk
  Revision
     28/08/2024
  SDS Version
     4.0
  Date of previous version
     28/06/2022 (3.0)
1.4. Emergency telephone number
  Contact the poison hotline: +45 82 12 12 12 (24 hour service)
  See section 4 "First aid measures".
SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
  Not classified according to Regulation (EC) No. 1272/2008 (CLP).
2.2. Label elements

    Hazard pictogram(s)

     Not applicable.
   Signal word
     Not applicable.
   Hazard statement(s)
```

```
Not applicable.
Precautionary statement(s)
```

```
General
```

```
-
Prevention
```

```
-
```

```
Response
```



Storage

-

Disposal

▼ Hazardous substances

bronopol (INN);2-bromo-2-nitropropane-1,3-diol

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

The product contains a biocidal product.

▼VOC

VOC content: 1 g/L

MAXIMUM VOC CONTENT (Phase II, category A/a (WB): 30 g/L)

2.3. Other hazards

▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. ▼ Substances

Not applicable. This product is a mixture.

Product/substance	Identifiers	% w/w	Classification	Note
Quartz (SiO2)	CAS No.: 14808-60-7 EC No.: 238-878-4 REACH: 01-2120770509-45-XXXX Index No.:	10-15%		
Titan dioxide > 10μm	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17 Index No.:	5-10%		
2-phenoxyethanol	CAS No.: 122-99-6 EC No.: 204-589-7 REACH: 01-2119488943-21-XXXX Index No.: 603-098-00-9	<1%	Acute Tox. 4, H302 Eye Dam. 1, H318 STOT SE 3, H335	
bronopol (INN);2-bromo-2- nitropropane-1,3-diol	CAS No.: 52-51-7 EC No.: 200-143-0 REACH: 01-2119980938-15-XXXX Index No.: 603-085-00-8	<0.05%	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT SE 3, H335 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)	
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3- one;1,2-benzisothiazolin-3- one	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: 01-2120761540-60-XXXX Index No.: 613-088-00-6	<0.01%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.036 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	



			Aquatic Chronic 1, H410 (M=1)
2-n-butyl-benzo[d]isothiazol-3 one	- CAS No.: 4299-07-4 EC No.: 420-590-7 REACH: 01-0000016721-74-XXXX Index No.: 606-079-00-3	<0.01%	Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH: Index No.: 613-167-00-5	<0.0015%	Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1, H317 (SCL: 0.0015 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 3, H331 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

▼ Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

▼ Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

▼ Burns

Not applicable.

4.2. ▼Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. ▼Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. ▼ Personal precautions, protective equipment and emergency procedures Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. ▼ Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. ▼ Reference to other sections

See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼ Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

Quartz (SiO2) Long term exposure limit (8 hours) (mg/m³): 0,1(respirabel) / 0,3(total) Short term exposure limit (15 minutes) (mg/m³): 0,2(respirabel) / 0,6(total) Annotations: E = Substance has an EC limit.

Titan dioxide > 10μm Long term exposure limit (8 hours) (mg/m³): 6 Short term exposure limit (15 minutes) (mg/m³): 12



Statutory order 291 on exposure limits for substances and mixtures (19/03/2024)

Quartz (SiO2) is included in the national list of substances suspected of causing cancer

BEK no. 290 of 19/03/2024 on measures to prevent the risk when working with carcinogenic, mutagenic or reproductively toxic substances and materials.

VDNEL

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

1,2-Delizisoti llazol-5(211)-011e, 1,2-Delizisoti llazoliti-5-011e, 1,2	-Delizisotillazolili-5-olie	
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	345 µg/kgbw/day
Long term – Systemic effects - Workers	Dermal	966 µg/kgbw/day
Long term – Systemic effects - General population	Inhalation	1.2 mg/m ³
Long term – Systemic effects - Workers	Inhalation	6.81 mg/m ³
bronopol (INN);2-bromo-2-nitropropane-1,3-diol		
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	4 µg/cm²
Long term – Local effects - Workers	Dermal	8 μg/cm ²
Long term – Systemic effects - General population	Dermal	700 µg/kgbw/day
Long term – Systemic effects - Workers	Dermal	2 mg/kg bw/day
Short term – Local effects - General population	Dermal	4 µg/cm ²
Short term – Local effects - Workers	Dermal	8 μg/cm ²
Short term – Systemic effects - General population	Dermal	2.1 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	6 mg/kg bw/day
Long term – Local effects - General population	Inhalation	600 µg/m³
Long term – Local effects - Workers	Inhalation	2.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	600 µg/m³
Long term – Systemic effects - Workers	Inhalation	3.5 mg/m ³
Short term – Local effects - General population	Inhalation	600 µg/m³
Short term – Local effects - Workers	Inhalation	2.5 mg/m ³
Short term – Systemic effects - General population	Inhalation	1.8 mg/m ³
Short term – Systemic effects - Workers	Inhalation	10.5 mg/m ³
Long term – Systemic effects - General population	Oral	180 µg/kgbw/day
Short term – Systemic effects - General population	Oral	500 μg/kgbw/day
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	2-methyl-2H-isothiazol-3-one (3	<u>۶</u> ۰۱)
Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 µg/m³
Long term – Local effects - Workers	Inhalation	20 µg/m³
Short term – Local effects - General population	Inhalation	40 µg/m³
Short term – Local effects - Workers	Inhalation	40 µg/m³
Long term – Systemic effects - General population	Oral	90 µg/kgbw/day
Short term – Systemic effects - General population	Oral	110 µg/kgbw/day
Γitan dioxide > 10μm		
Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	10 mg/m3



Long term – Systemic effects - General population	Oral	700 mg/kg bw/day
PNEC 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	;1,2-benzisothiazolin-3-one	
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		4.03 µg/L
Freshwater sediment		49.9 µg/kg
Intermittent release (freshwater)		1.1 μg/L
Intermittent release (marine water)		110 ng/L
Marine water		403 ng/L
Marine water sediment		4.99 µg/kg
Sewage treatment plant		1.03 mg/L
Soil		3 mg/kg
bronopol (INN);2-bromo-2-nitropropane-1,3-diol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1.25 µg/L
Freshwater sediment		21.5 µg/kg
Intermittent release (freshwater)		265 ng/L
Marine water		520 ng/L
Marine water sediment		8.944 µg/kg
Sewage treatment plant		430 µg/L
Soil		210 µg/kg
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one	and 2-methyl-2H-isothiazol-3-one (3:	1)
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.39 µg/L
Freshwater sediment		27 µg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L
Soil		10 µg/kg
Titan dioxide > 10μm		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	-	0,184 mg/l
Freshwater sediment	-	1000 mg/l
Intermittent release	-	0,193 mg/l
Marine water	-	0,0184 mg/l
Marine water sediment	-	100 mg/Kg
Sewage treatment plant	-	100 mg/l
Soil		100 mg/l

General recommendations Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios



There are no exposure scenarios implemented for this product.

▼ Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

▼ Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

 Measures to avoid environmental exposure No specific requirements.

Individual protection measures, such as personal protective equipment

▼ Generally

In the event the work process is within scope of the Danish statutory order on work with code numbered products (Work Inspectorate Order no. 302/1993), then personal protection equipment shall be selected as set out herein. If applicable, please refer to the code number of this product in section 15. Use only CE marked protective equipment.

▼ Respiratory Equipment

Туре	Class	Colour	Standards	
Combination filter A2P2	Class 2	Brown/White	EN14387	6

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	R

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 240	EN374-2, EN374-3, EN388	

▼ Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

```
9.1. Information on basic physical and chemical properties

Physical state
Liquid

Colour

White

Odour / Odour threshold
Faint
pH

8 - 9

V Density (g/cm<sup>3</sup>)

1,72 - 1,74 (20 °C)

Kinematic viscosity

No relevant or available data due to the nature of the product.

Particle characteristics

Does not apply to liquids.
```



Phase changes

- ▼ Melting point/Freezing point (°C)
- No relevant or available data due to the nature of the product. Softening point/range (°C)
 - Does not apply to liquids.
- ▼ Boiling point (°C)

No relevant or available data due to the nature of the product. Vapour pressure

- No relevant or available data due to the nature of the product.
- Relative vapour density No relevant or available data due to the nature of the product.
- ▼ Decomposition temperature (°C)

No relevant or available data due to the nature of the product. Data on fire and explosion hazards

▼ Flash point (°C)

No relevant or available data due to the nature of the product. Flammability (°C)

No relevant or available data due to the nature of the product. • Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product. • Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

Solubility

Solubility in water

Completely soluble

- ▼ n-octanol/water coefficient (LogKow)
 - No relevant or available data due to the nature of the product.
- Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

- 9.2. Other information
 - ▼VOC (g/L)
 - 1
 - ullet Other physical and chemical parameters
 - No data available.
 - Oxidizing properties

No relevant or available data due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. ▼ Reactivity

- No data available.
- 10.2. Chemical stability
 - The product is stable under the conditions, noted in section 7 "Handling and storage".
- 10.3. ▼ Possibility of hazardous reactions
 - None known.
- 10.4. ▼ Conditions to avoid None known.
- 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	Titan dioxide > 10µm
Species:	Rat



	Route of exposure: Test: Result:	Oral LD50 >5000 mg/Kg ·
	Product/substance Species:	Titan dioxide > 10µm Rat Inhalation
	Route of exposure: Test: Result:	Inhalation LC50 > 3,43 - 5,09 mg/l ·
	Product/substance Species: Route of exposure: Test: Result:	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one Rat Oral LD50 1193 mg/Kg ·
	Product/substance Species: Route of exposure: Test: Result:	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one Rat Dermal LD50 4115 mg/Kg ·
▼ :	Skin corrosion/irritation Product/substance Test method: Species: Result:	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one OECD 404 Rabbit Adverse effect observed (Irritating)
▼ :	Serious eye damage/irrit Product/substance Test method: Result:	ation 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one no guideline followed Adverse effect observed (Causes serious eye damage)
	spiratory sensitisation Based on available data Skin sensitisation	, the classification criteria are not met.
• •	Product/substance Species: Result: Other information:	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one Human Adverse effect observed (sensitising) Can course allergic reaction at skin contact
	Product/substance Test method: Other information:	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) OECD 406 Can course allergic reaction at skin contact
		, the classification criteria are not met.
	Carcinogenicity Based on available data Reproductive toxicity	, the classification criteria are not met.
	Based on available data OT-single exposure	, the classification criteria are not met.
ST	OT-repeated exposure	, the classification criteria are not met. , the classification criteria are not met.
	piration hazard	, the classification criteria are not met.
	Long term effects None known.	
	Endocrine disrupting pro This mixture/product do health. Other information	operties bes not contain any substances known to have hormone-disrupting properties in relation to



None known.

SECTION 12: Ecological information

12.1. ▼Toxicity

Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Test method:	OECD 201
Species:	Algae, Anabaena flos-aquae
Compartment:	Water
Duration:	72 hours
Test:	NOEC
Result:	0,0025 mg/L
Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Test method:	OECD 215
Species:	Fish, Oncorhynchus mykiss
Compartment:	Water
Duration:	28 days
Test:	NOEC
Result:	2,61 mg/L
Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Test method:	OECD 203
Species:	Fish, Lepomis macrochirus
Compartment:	Water
Duration:	96 hours
Test:	LC50
Result:	11 mg/L
Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Test method:	OECD 201
Species:	Algae, Anabaena flos-aquae
Compartment:	Water
Duration:	72 hours
Test:	EC50
Result:	0,068 mg/L
Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Test method:	OECD 202
Species:	Daphnia, Daphnia magna
Compartment:	Water
Duration:	48 hours
Test:	EC50
Result:	1,04 mg/L
Product/substance	Titan dioxide > 10μm
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	61 mg/l ·
Product/substance	Titan dioxide > 10μm
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	>1000 mg/l ·
2.1. ▼ Toxicity Product/substance Species: Duration: Test: Result:	Titan dioxide > 10μm Fish 96 hours LC50 >1000 mg/l ·



Test method:	OECD 209
Compartment:	Sewage treatment plant
Duration:	3 hours
Test:	EC50
Result:	11 mg/L
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	1,3 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Daphnia
Duration:	96 hours
Test:	EC50
Result:	1,5 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Algae
Duration:	48 hours
Test:	EC50
Result:	0,055 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	2,94 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Algae
Duration:	24 hours
Test:	EC50
Result:	0,11 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Fish
Duration:	No data available.
Test:	NOEC
Result:	0,21 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one
Species:	Daphnia
Duration:	21 days
Test:	NOEC
Result:	1,2 mg/l ·
Product/substance	2-n-butyl-benzo[d]isothiazol-3-one
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	0,15 mg/l ·
Product/substance	2-n-butyl-benzo[d]isothiazol-3-one
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	0,093 mg/l ·
Product/substance	2-n-butyl-benzo[d]isothiazol-3-one
Species:	Algae
Duration:	72 hours
Test:	ErC50



Result:	0,45 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Compartment:	Water
Duration:	72 hours
Test:	EC50
Result:	0,048 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 202
Species:	Daphnia, Daphnia magna
Compartment:	Water
Duration:	48 hours
Test:	EC50
Result:	0,1 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 201
Species:	Algae, Skeletonema costatum
Compartment:	Water
Duration:	48 hours
Test:	EC50
Result:	0,0052 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 203
Species:	Fish, Oncorhynchus mykiss
Compartment:	Water
Duration:	96 hours
Test:	LC50
Result:	0,22 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 211
Species:	Daphnia, Daphnia magna
Compartment:	Water
Duration:	21 days
Test:	NOEC
Result:	0,004 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 215
Species:	Fish, Oncorhynchus mykiss
Compartment:	Water
Duration:	28 days
Test:	NOEC
Result:	0,098 mg/L
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method:	OECD 209
Compartment:	Sewage treatment plant
Duration:	3 hours
Test:	EC50
Result:	7,92 mg/L
12.2. ▼ Persistence and d	egradability
Product/substance	bronopol (INN);2-bromo-2-nitropropane-1,3-diol
Compartment:	Water
Result:	70 %
Conclusion:	-
Test:	OECD 301 B
Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one



Conclusion:	Readily biodegradable
Product/substance Result: Conclusion:	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) 60 % -
Test:	OECD 301 D

12.3. ▼ Bioaccumulative potential

Product/substance	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one
LogKow:	1,3000
Conclusion:	No potential for bioaccumulation

12.4. ▼ Mobility in soil

No data available.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. ▼ Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. ▼Waste treatment methods

Product is not covered by regulations on dangerous waste.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

▼ EWC code

08 01 12

Waste paint and varnish other than those mentioned in 08 01 11

- ▼ Specific labelling
- Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / I	14.2 D UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. ▼ Special precautions for user

Not applicable.

14.7. ▼ Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Restrictions for application No special.
 - ▼ Demands for specific education



No specific requirements.

- SEVESO Categories / dangerous substances Not applicable.
- ▼ Regulation on work involving coded products Code number (1993): 00-1
- ▼ Additional information Not applicable.
- ▼ Sources

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products.

Executive Order no. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car repair painting.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

- H301, Toxic if swallowed.
- H302, Harmful if swallowed.
- H311, Toxic in contact with skin.
- H312, Harmful in contact with skin.
- H314, Causes severe skin burns and eye damage.
- H315, Causes skin irritation.
- H317, May cause an allergic skin reaction.
- H318, Causes serious eye damage.
- H319, Causes serious eye irritation.
- H331, Toxic if inhaled.
- H335, May cause respiratory irritation.
- H400, Very toxic to aquatic life.
- H410, Very toxic to aquatic life with long lasting effects.

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient



MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative

▼ Additional information

Not applicable.

The safety data sheet is validated by

MVP

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en