

772 Acrylic Filling Paint, Medium



Product information

Beck & Jørgensen A/S

Product Description

Filling Paint with medium structure for in- and exterior use.
The structure is depending of the tools and working process.

Directions for use

Walls: The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent.
Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Facades: The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Crack and holls shall be repaired with filler. Remove surface fouling with appropriate cleaner.
Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Technical data

Binder:	Acrylic
Type:	Filling paint with structure
Gloss:	Approx. 3 Flat matt
Vol. dry:	Approx. 42%
Colours:	White and B&J tinting system in light shades
Drying:	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water
Coverage:	2-8 m ² /ltr
Tools:	Brush or roller
Mal-Code:	00-1 (1993)

