773 Mosaik-Finish

Product information

Beck & Jorgensen A/S

Product Description

Semi matt clear lacquer for coloured chips for walls at staircases. To be used on most kind of wall paints and gives a cleanable surface.

Directions for use

The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion. Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces before painting.

The walls are painted with a wll paint gloss 6 or more in chosen colour.

Add 6-800 grams of chips in the lacquer and aply carefully in smooth layer with roller with short pile. Apply a second layer of lacquer witout chips to give a resistent surface.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass. Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed. Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed. Further information and MSDS on www.bj.dk

Remarks

It is not recommendable to use dark coloured wall paint.

Technical data

Binder:	Acrylic
Туре:	Clear lacquer for chips
Gloss:	
Vol. dry:	Approx. 22%
Colours:	Colourless
Drying:	1-2 hours, recoatable after approx. 16 hours at 20 ° C 65% RH.
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Should not be thinned
Coverage:	Approx. 10 m ² /ltr on planed wood
Tools:	brush and roller
Mal-Code:	00-1 (1993)



Rev. date: 20.01.2020 -

This product information is based on both practical and laboratory tests and is a guidance to choice of product and working method. Always use the latest version of the product information, which can be found on www.bj.dk. As we don't know about the workers working conditions, we do not bear responsibility for the final result.

Page: 1/1