

Product Description

Semi gloss high quality durable acrylic facade paint for facades and interior walls. The product appears with a resistant and durable surface and a high gloss and colour retention.

Suitable for facades of plaster, concrete and primed metal.

Contains materials, that protect the film against surface mold.

Directions for use

Walls: The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Remove dirt, dust and loose material. Wash down previously painted surfaces with appropriate detergent. Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Facades: The substrate must be clean, dry and sound / stable and free from all substances that may prevent good adhesion.

Crack and holls shall be repaired with filler.

Priming of porous and water absorbing surfaces with Microprimer 716 or similar is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless and roller	17-21 (Graco)			60mesh

Technical data

Binder: Acrylic

Type: Acrylic facade paint / Acrylic Wall paint

Gloss:

Vol. dry:

Colours:

Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoatable after app. 8 hours.

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water

Coverage: 8-10 m²/ltr

Tools: Brush, roller or airless

Mal-Code: 00-1 (1993)

