

SAFETY DATA SHEET

774 Satin

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

774 Satin

Product no.

774xxx

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Beck & Jørgensen A/S

Rosenkaeret 25-29

DK-2860 Søborg

Denmark

Tel: +45 39 53 03 11

Contact person

Mikael Jensen

E-mail

miljo@bj.dk

Revision

10/09/2024

SDS Version

3.0

Date of previous version

10/09/2024 (3.0)

1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

-

Prevention

Avoid release to the environment. (P273)

Response



Storage

. .

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

bronopol (INN);2-bromo-2-nitropropane-1,3-diol

3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate terbutyn

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

▼Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

This paint contains a biocidal product for the preservation of the dry film.

VOC

VOC content: 1 q/L

MAXIMUM VOC CONTENT (Phase II, category A/d (WB): 130 g/L)

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

| Product/substance | Identifiers | % w/w | Classification | Note |
|---|--|--------|--|------|
| Titan dioxide > 10μm | CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17 Index No.: | 15-25% | | |
| bronopol (INN);2-bromo-2- nitropropane-1,3-diol | CAS No.: 52-51-7 EC No.: 200-143-0 REACH: 01-2119980938-15-XXXX Index No.: 603-085-00-8 | <0.05% | Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT SE 3, H335 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10) | |
| 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2- yn-1-yl butylcarbamate | CAS No.: 55406-53-6 EC No.: 259-627-5 REACH: Index No.: 616-212-00-7 | <0.05% | Acute Tox. 4, H302 (ATE: 1056.00 mg/kg) Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) | |
| terbutryn | CAS No.: 886-50-0 EC No.: 212-950-5 REACH: Index No.: | <0.05% | Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) | |



| 1,2-benzisothiazol-3(2H)-one; | CAS No.: 2634-33-5 | <0.01% | Acute Tox. 4, H302 |
|-------------------------------|------------------------------|-----------------|---|
| 1,2-benzisothiazolin-3- | EC No.: 220-120-9 | ~0.01 70 | Skin Irrit. 2, H315 |
| one;1,2-benzisothiazolin-3- | REACH: 01-2120761540-60-XXXX | | Skin Sens. 1, H317 (SCL: 0.036 %) |
| one | Index No.: 613-088-00-6 | | Eye Dam. 1, H318 |
| one | 11dex 140 013-088-00-0 | | Aquatic Acute 1, H400 (M=1) |
| | | | • |
| | | | Aquatic Chronic 1, H410 (M=1) |
| reaction mass of 5-chloro-2- | CAS No.: 55965-84-9 | <0.0015% | Acute Tox. 3, H301 |
| methyl-2H-isothiazol-3-one | EC No.: 611-341-5 | | Acute Tox. 3, H311 |
| and 2-methyl-2H-isothiazol-3- | REACH: | | Skin Corr. 1B, H314 (SCL: 0.60 %) |
| one (3:1) | Index No.: 613-167-00-5 | | Skin Irrit. 2, H315 (SCL: 0.06 %) |
| | | | Skin Sens. 1, H317 (SCL: 0.0015 %) |
| | | | Eye Irrit. 2, H319 (SCL: 0.06 %) |
| | | | Acute Tox. 3, H331 |
| | | | Aquatic Acute 1, H400 (M=1) |
| | | | Aguatic Chronic 1, H410 (M=1) |

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 $^{\circ}$ C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titan dioxide > 10µm

Long term exposure limit (8 hours) (mg/m³): 6

Short term exposure limit (15 minutes) (mg/m³): 12

2-butoxyethanol; ethylene glycol monobutyl ether



Long term exposure limit (8 hours) (mg/m³): 98 Long term exposure limit (8 hours) (ppm): 20 Short term exposure limit (15 minutes) (mg/m³): 246 Short term exposure limit (15 minutes) (ppm): 50 Annotations:

E = Substance has an EC limit.

H = The substance can be absorbed through the skin.

Statutory order 291 on exposure limits for substances and mixtures (19/03/2024)

DNEL

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

| Duration: | Route of exposure: | DNEL: |
|---|--------------------|-----------------|
| Long term – Systemic effects - General population | Dermal | 345 μg/kgbw/day |
| Long term – Systemic effects - Workers | Dermal | 966 µg/kgbw/day |
| Long term – Systemic effects - General population | Inhalation | 1.2 mg/m³ |
| Long term – Systemic effects - Workers | Inhalation | 6.81 mg/m³ |

2-butoxyethanol; ethylene glycol monobutyl ether

| Duration: | Route of exposure: | DNEL: |
|--|--------------------|-------------------|
| Long term – Systemic effects - General population | Inhalation | 59 mg/m³ |
| Long term – Systemic effects - Workers | Inhalation | 98 mg/m³ |
| Short term – Local effects - General population | Inhalation | 147 mg/m³ |
| Short term – Local effects - Workers | Inhalation | 246 mg/m³ |
| Short term – Systemic effects - General population | Inhalation | 426 mg/m³ |
| Short term – Systemic effects - Workers | Inhalation | 1091 mg/m³ |
| Long term – Systemic effects - General population | Oral | 6.3 mg/kg bw/day |
| Short term – Systemic effects - General population | Oral | 26.7 mg/kg bw/day |

bronopol (INN);2-bromo-2-nitropropane-1,3-diol

| Duration: | Route of exposure: | DNEL: |
|--|--------------------|------------------------|
| Long term – Local effects - General population | Dermal | 4 μg/cm² |
| Long term – Local effects - Workers | Dermal | 8 μg/cm² |
| Long term – Systemic effects - General population | Dermal | 700 μg/kgbw/day |
| Long term – Systemic effects - Workers | Dermal | 2 mg/kg bw/day |
| Short term – Local effects - General population | Dermal | 4 μg/cm² |
| Short term – Local effects - Workers | Dermal | 8 μg/cm² |
| Short term – Systemic effects - General population | Dermal | 2.1 mg/kg bw/day |
| Short term – Systemic effects - Workers | Dermal | 6 mg/kg bw/day |
| Long term – Local effects - General population | Inhalation | 600 μg/m³ |
| Long term – Local effects - Workers | Inhalation | 2.5 mg/m³ |
| Long term – Systemic effects - General population | Inhalation | 600 μg/m³ |
| Long term – Systemic effects - Workers | Inhalation | 3.5 mg/m ³ |
| Short term – Local effects - General population | Inhalation | 600 μg/m³ |
| Short term – Local effects - Workers | Inhalation | 2.5 mg/m³ |
| Short term – Systemic effects - General population | Inhalation | 1.8 mg/m³ |
| Short term – Systemic effects - Workers | Inhalation | 10.5 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 180 μg/kgbw/day |
| Short term – Systemic effects - General population | Oral | 500 μg/kgbw/day |

Fatty alcohol ethoxylate



| Duration: | Route of exposure: | DNEL: |
|--|--|--|
| Long term – Systemic effects - General population | Dermal | 66.7 mg/kg bw/da |
| Long term – Systemic effects - Workers | Dermal | 187 mg/kg bw/da |
| Long term – Systemic effects - General population | Inhalation | 3.48 mg/m ³ |
| Long term – Systemic effects - Workers | Inhalation | 19.6 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 1.33 mg/kg bw/da |
| propylidyntrimethanol | | |
| Duration: | Route of exposure: | DNEL: |
| Long term – Systemic effects - General population | Dermal | 340 μg/kgbw/day |
| Long term – Systemic effects - Workers | Dermal | 940 μg/kgbw/day |
| Long term – Systemic effects - General population | Inhalation | 580 μg/m³ |
| Long term – Systemic effects - Workers | Inhalation | 3.3 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 340 µg/kgbw/day |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-ı | methyl-2H-isothiazol-3-one (3:1 |) |
| Duration: | Route of exposure: | DNEL: |
| Long term – Local effects - General population | Inhalation | 20 μg/m³ |
| Long term – Local effects - Workers | Inhalation | 20 μg/m³ |
| Short term – Local effects - General population | Inhalation | 40 μg/m³ |
| Short term – Local effects - Workers | Inhalation | 40 μg/m³ |
| Long term – Systemic effects - General population | Oral | 90 μg/kgbw/day |
| Short term – Systemic effects - General population | Oral | 110 μg/kgbw/day |
| Titan dioxide > 10μm | | |
| Duration: | Route of exposure: | DNEL: |
| Long term – Local effects - Workers | Inhalation | 10 mg/m3 |
| Long term – Systemic effects - General population | Oral | 700 mg/kg bw/da |
| EC | | |
| 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylca | | |
| Route of exposure: | Duration of Exposure: | PNEC: |
| Soil | Single | 0,005 mg/l |
| | C: I - | 0,0005 mg/l |
| Water | Single | 0,0003 1119/1 |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be | enzisothiazolin-3-one | |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be | - | PNEC: |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: | enzisothiazolin-3-one | |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: | enzisothiazolin-3-one | PNEC: |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: Freshwater Freshwater sediment | enzisothiazolin-3-one | PNEC: 4.03 μg/L |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: Freshwater Freshwater sediment Intermittent release (freshwater) | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: Freshwater Freshwater sediment Intermittent release (freshwater) Intermittent release (marine water) | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: Freshwater Freshwater sediment Intermittent release (freshwater) Intermittent release (marine water) Marine water | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L 110 ng/L |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazol | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L 110 ng/L 403 ng/L |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazol | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L 110 ng/L 403 ng/L 4.99 μg/kg |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazol | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L 110 ng/L 403 ng/L 4.99 μg/kg 1.03 mg/L |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazol | enzisothiazolin-3-one | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L 110 ng/L 403 ng/L 4.99 μg/kg 1.03 mg/L |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-be Route of exposure: Freshwater Freshwater sediment Intermittent release (freshwater) Intermittent release (marine water) Marine water Marine water sediment Sewage treatment plant Soil 2-butoxyethanol; ethylene glycol monobutyl ether | enzisothiazolin-3-one Duration of Exposure: | PNEC: 4.03 μg/L 49.9 μg/kg 1.1 μg/L 110 ng/L 403 ng/L 4.99 μg/kg 1.03 mg/L 3 mg/kg |



| ntermittent release (freshwater) | | 26.4 mg/L |
|---|--|-------------|
| Marine water | | 880 μg/L |
| Marine water sediment | | 3.46 mg/kg |
| redators | | 20 mg/kg |
| ewage treatment plant | | 463 mg/L |
| oil | | 2.33 mg/kg |
| ronopol (INN);2-bromo-2-nitropropane-1,3-diol | | |
| oute of exposure: | Duration of Exposure: | PNEC: |
| reshwater | | 1.25 μg/L |
| reshwater sediment | | 21.5 μg/kg |
| ntermittent release (freshwater) | | 265 ng/L |
| Marine water | | 520 ng/L |
| Marine water sediment | | 8.944 µg/kg |
| ewage treatment plant | | 430 μg/L |
| oil | | 210 μg/kg |
| atty alcohol ethoxylate | | |
| coute of exposure: | Duration of Exposure: | PNEC: |
| reshwater | · | 3.4 µg/L |
| reshwater sediment | | 89.5 µg/kg |
| ntermittent release (freshwater) | | 445 ng/L |
| ntermittent release (marine water) | | 44.5 ng/L |
| Marine water | | 340 ng/L |
| Marine water sediment | | 8.95 µg/kg |
| ewage treatment plant | | 200 μg/L |
| oil | | 16 µg/kg |
| eaction mass of 5-chloro-2-methyl-2H-isothiazol-3-o | one and 2-methyl-2H-isothiazol-3-one (3: | 1) |
| oute of exposure: | Duration of Exposure: | PNEC: |
| reshwater | · | 3.39 µg/L |
| reshwater sediment | | 27 μg/kg |
| ntermittent release (freshwater) | | 3.39 µg/L |
| ntermittent release (marine water) | | 3.39 µg/L |
| Marine water | | 3.39 µg/L |
| Marine water sediment | | 27 μg/kg |
| ewage treatment plant | | 230 μg/L |
| oil | | 10 μg/kg |
| itan dioxide > 10μm | | |
| coute of exposure: | Duration of Exposure: | PNEC: |
| reshwater | | 0,184 mg/l |
| reshwater sediment | - | 1000 mg/l |
| ntermittent release | - | 0,193 mg/l |
| Marine water | - | 0,0184 mg/l |
| | | 100 mg/Kg |
| Marine water sediment | <u>-</u> | 100 mg/kg |
| Marine water sediment ewage treatment plant | - | 100 mg/l |



8.2. Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

In the event the work process is within scope of the Danish statutory order on work with code numbered products (Work Inspectorate Order no. 302/1993), then personal protection equipment shall be selected as set out herein. If applicable, please refer to the code number of this product in section 15.

Use only CE marked protective equipment.

Respiratory Equipment

| Туре | Class | Colour | Standards | |
|------|-------|--------|-----------|--|
| S/SL | P2 | White | EN149 | |

Skin protection

| Recommended | Type/Category | Standards | |
|--|---------------|-----------|---|
| Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product. | - | - | P |



Hand protection

| Material | Glove thickness (mm) | Breakthrough time (min.) | Standards | |
|----------|----------------------|-----------------------------|-------------------------|--|
| Nitrile | 0.4 | > 480 | EN374-2, EN374-3, EN388 | |



Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Various colours

Odour / Odour threshold

Faint

рН

8,0 - 8,8

Density (g/cm³)

1,26 - 1,28 (20 °C)



Kinematic viscosity

No relevant or available data due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No relevant or available data due to the nature of the product.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

No relevant or available data due to the nature of the product.

Vapour pressure

No relevant or available data due to the nature of the product.

Relative vapour density

No relevant or available data due to the nature of the product.

Decomposition temperature (°C)

No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

No relevant or available data due to the nature of the product.

Flammability (°C)

No relevant or available data due to the nature of the product.

Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product.

Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

VOC (g/L)

1

Other physical and chemical parameters

No data available.

Oxidizing properties

No relevant or available data due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information



11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Titan dioxide > 10µm

Species: Rat Route of exposure: Oral Test: LD50

>5000 mg/Kg · Result:

Product/substance Titan dioxide > 10µm

Species: Route of exposure: Inhalation LC50 Test:

Result: > 3,43 - 5,09 mg/l ·

Product/substance Fatty alcohol ethoxylate

Species: Rat Route of exposure: Oral

Test:

Result: > 300 - 2000 mg/kg ·

Product/substance terbutryn

Species: Rat Route of exposure: Oral LD50 Test:

Result: 2045 mg/Kg ·

Product/substance terbutryn

Species: Mouse Route of exposure: Oral Test: LD50

Result: 3884 mg/Kg ·

Product/substance

terbutryn Species: Rabbit Route of exposure: Dermal Test: LD50

 $> 10200 \text{ mg/Kg} \cdot$ Result:

Product/substance terbutryn Species: Rat Route of exposure: Inhalation LC50 Test:

Result: >5,34 mg/l (4 h) ·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

Species: Rat Route of exposure: Oral LD50 Test:

Result: 1193 mg/Kg ·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

Species: Rat Route of exposure: Dermal Test: LD50 Result: 4115 mg/Kg ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Rabbit Species: Route of exposure: Dermal LD50 Test: 210 mg/kg · Result:

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Rabbit Species:



Route of exposure: Oral
Test: LD50
Result: 300 mg/kg

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: 2,21 mg/l/4h

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Species: Rat Route of exposure: Oral Test: LD50

Result: > 200 -< 2000 mg/kg ·

Product/substance 5-chloro-2-methyl-2H-isothiazol-3-one

 Species:
 Rat

 Route of exposure:
 Oral

 Test:
 LD50

 Result:
 550 mg/kg

Product/substance 5-chloro-2-methyl-2H-isothiazol-3-one

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: 1000 mg/kg

Product/substance 5-chloro-2-methyl-2H-isothiazol-3-one

Species: Rat
Route of exposure: Inhalation
Test: LC50 (4 hours)
Result: 0,31 mg/L

Skin corrosion/irritation

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Test method: OECD 404 Species: Rabbit

Result: Adverse effect observed (Irritating)

Serious eye damage/irritation

Product/substance Fatty alcohol ethoxylate
Test method: roguideline followed

Species: Rabbit

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Test method: no guideline followed

Result: Adverse effect observed (Causes serious eye damage)

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Species: Human

Result: Adverse effect observed (sensitising)
Other information: Can course allergic reaction at skin contact

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 406

Other information: Can course allergic reaction at skin contact

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.



Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance Titan dioxide > 10µm

Species: Fish
Duration: 96 hours
Test: LC50
Result: >1000 mg/l⋅

Product/substance Titan dioxide > 10µm

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: >1000 mg/l·

Product/substance Titan dioxide > 10µm

Species: Algae
Duration: 72 hours
Test: EC50
Result: 61 mg/l·

Product/substance Fatty alcohol ethoxylate

 Species:
 Algae

 Duration:
 72 hours

 Test:
 EC0

 Result:
 0,1 < 1 mg/l·</td>

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Test method: OECD 202

Species: Daphnia, Daphnia magna

Compartment: Water
Duration: 48 hours
Test: EC50
Result: 1,04 mg/L

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Test method: OECD 201

Species: Algae, Anabaena flos-aquae

Compartment: Water
Duration: 72 hours
Test: EC50
Result: 0,068 mg/L

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Test method: OECD 203



Species: Fish, Lepomis macrochirus

Compartment: Water
Duration: 96 hours
Test: LC50
Result: 11 mg/L

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Test method: OECD 215

Species: Fish, Oncorhynchus mykiss

Compartment: Water
Duration: 28 days
Test: NOEC
Result: 2,61 mg/L

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Test method: OECD 201

Species: Algae, Anabaena flos-aquae

Compartment: Water
Duration: 72 hours
Test: NOEC
Result: 0,0025 mg/L

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Test method: OECD 209

Compartment: Sewage treatment plant

Duration: 3 hours
Test: EC50
Result: 11 mg/L

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species: Fish
Duration: 96 hours
Test: LC50
Result: 0,049 mg/l⋅

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 0,160 mg/l·

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species:AlgaeDuration:72 hoursTest:IC50Result:0,022 mg/l·

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species: Daphnia
Duration: 21 days
Test: NOEC
Result: 1,3 mg/l·

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species: Fish
Duration: 21 days
Test: NOEC
Result: 0,01 mg/l·

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species:DaphniaDuration:21 daysTest:EC50Result:0,05 mg/l ·



Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species: Fish
Duration: 35 d.
Test: NOEC

Result: 0,0084 mg/l·

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Species: Algae
Duration: 72 hours
Test: NOEC
Result: 0,0046 mg/l·

Product/substance terbutryn
Species: Algae
Duration: 7 days
Test: EC50
Result: 0,013 mg/l·

Product/substance terbutryn
Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 2,66 mg/l·

Product/substance terbutryn
Species: Fish
Duration: 96 hours
Test: LC50
Result: 0,067 mg/l·

Product/substance terbutryn
Species: Daphnia
Duration: 21 days
Test: NOEC
Result: 1,3 mg/l·

Product/substance terbutryn
Species: Fish
Duration: 35 d.
Test: NOEC
Result: 0,84 mg/l·

Product/substance terbutryn
Species: Fish
Duration: 21 days
Test: NOEC
Result: 0,01 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

Species: Fish
Duration: 96 hours
Test: LC50
Result: 1,3 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Species:DaphniaDuration:96 hoursTest:EC50Result:1,5 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

Species: Algae Duration: 48 hours



Test: EC50

Result: 0,055 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: 2,94 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

Species: Algae
Duration: 24 hours
Test: EC50
Result: 0,11 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Species: Fi

Duration: No data available.

Test: NOEC Result: 0,21 mg/l·

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Species: Daphnia
Duration: 21 days
Test: NOEC
Result: 1,2 mg/l·

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 20

Species: Algae, Pseudokirchneriella subcapitata

Compartment: Water
Duration: 72 hours
Test: EC50
Result: 0,048 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 202

Species: Daphnia, Daphnia magna

Compartment: Water
Duration: 48 hours
Test: EC50
Result: 0,1 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 201

Species: Algae, Skeletonema costatum

Compartment: Water
Duration: 48 hours
Test: EC50
Result: 0,0052 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 203

Species: Fish, Oncorhynchus mykiss

Compartment: Water
Duration: 96 hours
Test: LC50
Result: 0,22 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 211

Species: Daphnia, Daphnia magna

Compartment: Water
Duration: 21 days
Test: NOEC



Result: 0,004 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 215

Species: Fish, Oncorhynchus mykiss

Compartment: Water
Duration: 28 days
Test: NOEC
Result: 0,098 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Test method: OECD 209

Compartment: Sewage treatment plant

Duration: 3 hours
Test: EC50
Result: 7,92 mg/L

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Species: Fish
Duration: 96 hours
Test: LC50

Result: 820 - 1490 mg/l ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Species:DaphniaDuration:48 hoursTest:EC50

Result: 835 - 1550 mg/l ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Species: Algae
Duration: 72 hours
Test: IC50
Result: 1840 mg/l·

Product/substance 5-chloro-2-methyl-2H-isothiazol-3-one Species: Algae, Pseudokirchneriella subcapitata

Compartment: Water
Duration: 72 hours
Test: EC50
Result: 0,018 mg/L

Product/substance 5-chloro-2-methyl-2H-isothiazol-3-one

Species: Daphnia, Daphnia magna

Compartment: Water
Duration: 48 hours
Test: EC50
Result: 0,16 mg/L

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Product/substance Fatty alcohol ethoxylate Conclusion: Fatty biodegradable

Product/substance bronopol (INN);2-bromo-2-nitropropane-1,3-diol

Compartment: Water Result: 70 % Conclusion: -

Test: OECD 301 B

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

Conclusion: Readily biodegradable

Product/substance terbutryn



Conclusion: Not biodegradable

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 1,2-benzisothiazolin-3-one

Conclusion: Readily biodegradable

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Result: 60 % Conclusion: -

Test: OECD 301 D

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

Result: 88% efter 28 dage
Conclusion: Readily biodegradable

Test: OECD 301 C

12.3. Bioaccumulative potential

Product/substance 3-iodo-2-propynyl butylcarbamate 3-iodoprop-2-yn-1-yl butylcarbamate

LogKow: 2,8100

Conclusion: No potential for bioaccumulation

Product/substance terbutryn LogKow: 3,6900 Conclusion: -

Product/substance 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one;1,2-benzisothiazolin-3-one

LogKow: 1,3000

Conclusion: No potential for bioaccumulation

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether

BCF: 2,5 LogKow: 0,8000

Conclusion: No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information



| | 14.1 UN / I | 14.2 D UN proper shipping name | 14.3 Hazard class(es) | 14.4 PG* | 14.5 Env** | Other information: |
|------|----------------|-----------------------------------|--------------------------|-------------|---------------|--------------------|
| ADR | - | - | - | - | - | - |
| IMDG | - | - | - | - | - | - |
| IATA | - | - | - | - | - | - |

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Regulation on work involving coded products

Code number (1993): 00-1

Additional information

Not applicable.

Sources

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products.

Executive Order no. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car repair painting.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H272, May intensify fire; oxidiser.

H290, May be corrosive to metals.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H310, Fatal in contact with skin.

H311, Toxic in contact with skin.

H312. Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

^{**} Environmental hazards



H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H331, Toxic if inhaled.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H341, Suspected of causing genetic defects.

H350, May cause cancer.

H361, Suspected of damaging fertility or the unborn child.

H361f, Suspected of damaging fertility.

H361fd, Suspected of damaging fertility or the unborn child.

H372, Causes damage to organs through prolonged or repeated exposure.

H373, May cause damage to organs through prolonged or repeated exposure.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

H413, May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).



The safety data sheet is validated by

MII

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en