

Product information

Beck & Jorgensen A/S

Product Description

Semi-matte acrylic paint with a rustic, metallizing and resistant surface. Can be used in- and exterio. To be used primarily for woodwork and metal, but also suitable as decorative paint on eg. walls

Directions for use

Metal: Remove dirt, dust grease and rust. Sand or preferably sandblast to SA 2½. Prime with appropriate primer according to instruction and finish with 2-3 times topcoat.

Exterior woodwork, which needs protection against wood-destroying fungus, should be primed prior to treatment with the final product with an appropriate preservative.

Pressure and vacuum impregnated wood of good sound quality can be treated directly after drying with the described product. If needed degrease resin and knots with an appropriate thinners. Saturate end grain thoroughly with an appropriate preservative.

Interior walls:Remove dirt, dust and loose material, and other material that prevents sufficient adherens. Wash down previously painted surfaces with with appropriate detergent. Priming of porous and water absorbing surfaces with Mikrodispers 716 is recommended.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass. Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed. Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed. Further information and MSDS on www.bj.dk

Remarks

Due to the metallic effect the paint can be shimmering

Sprayguide

| Spraying Nozzie Air pressure Ass. Air Fliter | Spraying | Nozzle | Air pressure | Ass. Air | Filter |
|----------------------------------------------|----------|--------|--------------|----------|--------|
|----------------------------------------------|----------|--------|--------------|----------|--------|

Technical data

| Binder: | Acrylic | |
|--------------|--------------------------------------------------------------------|---------------------|
| Туре: | | CDACITA |
| Gloss: | Semi matt, metallic | ACTIVIDANTIALING WA |
| Vol. dry: | App. 35% | Halvmat, Meta |
| Colours: | Silver and some special colours | 775 |
| Drying: | App. 2-4 hours at 20° C. RH.: 65%. Recoateable after app. 8 hours. | Beck & Jorgensen A |
| Application: | +10 °C to + 25° C. RH: 40-80% | |
| Thinning: | Water | |
| Coverage: | Approx. 10 m ² /ltr on planed wood | |
| Tools: | Brush, Roller or Spraying | |
| Mal-Code: | 00-1 (1993) | |

Page: 1/1

Rev. date: 20.01.2020 -

This product information is based on both practical and laboratory tests and is a guidance to choice of product and working method. Always use the latest version of the product information, which can be found on www.bj.dk. As we don't know about the workers working conditions, we do not bear responsibility for the final result.