

784 Pari-Dan, Gloss 30 Water-borne



Product information

Beck & Jorgensen A/S

Product Description

Semi-gloss acrylic enamel with good leveling, which appears with a hard, smooth and easy to clean surface. Suitable for indoor wood and iron, for example. frames, panels, doors and the like.

Pari-Dan 784 meets the requirements of the EU Eco-label Flower of all shades, provided the product is tinted with B & J Tinting System Monicolor.

Directions for use

The substrate must be clean, dry and stable. Soiled surfaces should be cleaned with suitable cleaner.

New wood should be primed with suitable water-borne primer. If necessary, use a suitable undercoat, followed by 2 coats of the finished paint Pari-Dan Aqueous.

Previously painted surfaces to be prepared and suitable for applying the top coat before applying the top coat. Iron and metal should be primed with suitable primer before applying the top coat.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

This product has been qualified for the EU Eco-label by reducing the water and air pollution as well as the quantity of waste.

Further information on why this product was assigned with EU Eco-label can be found on www.ecolabel.eu

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless with Finefinish	10-14 (graco)			100 mesh

Technical data

Binder:	Acrylic
Type:	Acrylic Enamel
Gloss:	Approx. 30, semigloss
Vol. dry:	App. 35%
Colours:	White, can be tinted with B&J tinting colours
Drying:	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water. Normally not to be diluted
Coverage:	8-10 m ² /ltr
Tools:	Brush, Roller or Spraying
Mal-Code:	00-1 (1993)

