

Product Description

High solid thixotropic trim pant with high filling capacity.

Easy to use for interior woodworks, as doors and panels. Du to the binder the product is not recommendable for radiators and window sills.

Directions for use

The substrate must be clean, dry and stable. Soiled surfaces should be cleaned with suitable cleaner.

New wood should be primed with suitable water-borne primer. If necessary, use a suitable undercoat, followed by 2 coats of the finished paint S-Enamel Aqueous.

Previously painted surfaces to be prepared and suitable for applying the top coat before applying the top coat. Iron and metal should be primed with suitable primer before applying the top coat.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

The get the best finish apply sufficient material.

Technical data

Binder:	Acrylic
Type:	Acrylic Enamel
Gloss:	Approx. 40 Semi gloss
Vol. dry:	App. 35%
Colours:	White, can be tinted with B&J tinting colours
Drying:	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
Application:	+10 °C to + 25° C. RH: 40-80%
Thinning:	Water
Coverage:	Rough saw timber: 2-5 m ² /Liter Planed timber: 8-10 m ² /Liter
Tools:	brush and roller
Mal-Code:	00-1 (1993)

