

## SAFETY DATA SHEET

# 788 TIX 40

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

788 TIX 40

Product no.

788101

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Water-borne acrylic enamel for interior use

Uses advised against

Acrylmaling vandig

#### 1.3. Details of the supplier of the safety data sheet

Company and address

**Beck & Jørgensen A/S**

Rosenkaeret 25-29

DK-2860 Søborg

Denmark

Tel: +45 39 53 03 11

Contact person

Mikael Jensen

E-mail

miljo@bj.dk

Revision

14/10/2025

SDS Version

1.0

#### 1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

#### 2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

Not applicable.

#### Prevention

Not applicable.

#### Response

Not applicable.

#### Storage

Not applicable.

#### Disposal

Not applicable.

#### Hazardous substances

1,2-benzisothiazol-3(2H)-one;

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

#### Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1),

1,2-benzisothiazol-3(2H)-one; . May produce an allergic reaction.

EUH210, Safety data sheet available on request.

The product contains a biocidal product.

#### VOC

VOC content: 25 g/L

MAXIMUM VOC CONTENT (Phase II, category A/d (WB): 130 g/L)

#### 2.3. Other hazards

##### Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Titan dioxide > 10µm	CAS No.: 13463-67-7 EC No.: 236-675-5 REACH: 01-2119489379-17 Index No.:	15-25%		
propane-1,2-diol	CAS No.: 57-55-6 EC No.: 200-338-0 REACH: 01-2119456809-23-XXXX Index No.:	1-3%		
ammonia ....%	CAS No.: 1336-21-6 EC No.: 215-647-6 REACH: 01-2119488876-14 Index No.: 007-001-01-2	<0.25%	Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	
1,2-benzisothiazol-3(2H)-one;	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: 01-2120761540-60-XXXX Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.036 %) Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH:	<0.0015%	Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 (SCL: 0.60 %)	

and 2-methyl-2H-isothiazol-3-one (3:1)

Skin Irrit. 2, H315 (SCL: 0.06 %)  
Skin Sens. 1, H317 (SCL: 0.0015 %)  
Eye Irrit. 2, H319 (SCL: 0.06 %)  
Acute Tox. 3, H331  
Aquatic Acute 1, H400 (M=100)  
Aquatic Chronic 1, H410 (M=100)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

In case of discomfort: bring the person into fresh air.

##### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

##### Eye contact

Rinse gently with lukewarm water. Remove any contact lenses if this is easy to do. Continue rinsing. In case of persistent eye irritation or discomfort: Seek medical help.

##### Ingestion

Rinse and flush mouth thoroughly and consume large quantities of water. In case of continued discomfort: seek medical assistance and bring this safety data sheet.

##### Burns

Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

No specific requirements.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage conditions

Room temperature 18 to 23°C

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Titan dioxide > 10µm

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 6

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 12

ammonia ....%

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 14

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 36

Short term exposure limit (15 minutes) (ppm): 50

ethanediol ethylene glycol

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 26 / 10 (forstøvet)

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 104 / 20 (forstøvet)

Short term exposure limit (15 minutes) (ppm): 40

Annotations:

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

E = Substance has an EC limit.

H = The substance can be absorbed through the skin.

2-butoxyethanol; ethylene glycol monobutyl ether

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 98

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 246

Short term exposure limit (15 minutes) (ppm): 50

Annotations:

E = Substance has an EC limit.

H = The substance can be absorbed through the skin.

Statutory order 1619 on exposure limits for substances and mixtures (19/12/2024)

## DNEL

ethanediol ethylene glycol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	53 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	106 mg/kg bw/day
Long term – Local effects - General population	Inhalation	7 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	35 mg/m <sup>3</sup>

1,2-benzisothiazol-3(2H)-one;

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	345 µg/kg bw/day
Long term – Systemic effects - Workers	Dermal	966 µg/kg bw/day
Long term – Systemic effects - General population	Inhalation	1.2 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	6.81 mg/m <sup>3</sup>

2-butoxyethanol; ethylene glycol monobutyl ether

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	98 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	147 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	246 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	426 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1091 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

ammonia ....%

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	68 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	6,8 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	68 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	6,8 mg/kg bw/day
Long term – Local effects - General population	Inhalation	2,8 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	14 mg/m <sup>3</sup>

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Systemic effects - General population	Inhalation	23,8 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	47,6 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	7,2 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	36 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	23,8 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	47,6 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6,8 mg/kg bw/day
Short term – Systemic effects - General population	Oral	6,8 mg/kg bw/day

#### propane-1,2-diol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	10 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	10 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	50 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	168 mg/m <sup>3</sup>

#### propylidyntrimethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	340 µg/kg bw/day
Long term – Systemic effects - Workers	Dermal	940 µg/kg bw/day
Long term – Systemic effects - General population	Inhalation	580 µg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	3.3 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	340 µg/kg bw/day

#### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 µg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	20 µg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	40 µg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	40 µg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	90 µg/kg bw/day
Short term – Systemic effects - General population	Oral	110 µg/kg bw/day

#### Titan dioxide > 10µm

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	10 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	700 mg/kg bw/day

#### PNEC

##### ethanediol ethylene glycol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		10 mg/L
Freshwater sediment		37 mg/kg
Intermittent release (freshwater)		10 mg/L
Intermittent release (marine water)		10 mg/L
Marine water		1 mg/L

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Marine water sediment		3.7 mg/kg
Sewage treatment plant		199.5 mg/L
Soil		1.53 mg/kg
1,2-benzisothiazol-3(2H)-one;		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		4.03 µg/L
Freshwater sediment		49.9 µg/kg
Intermittent release (freshwater)		1.1 µg/L
Intermittent release (marine water)		110 ng/L
Marine water		403 ng/L
Marine water sediment		4.99 µg/kg
Sewage treatment plant		1.03 mg/L
Soil		3 mg/kg
2-butoxyethanol; ethylene glycol monobutyl ether		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Intermittent release (freshwater)		26.4 mg/L
Marine water		880 µg/L
Marine water sediment		3.46 mg/kg
Predators		20 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg
propane-1,2-diol		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		260 mg/L
Freshwater sediment		572 mg/kg
Intermittent release (freshwater)		183 mg/L
Marine water		26 mg/L
Marine water sediment		57.2 mg/kg
Sewage treatment plant		20 g/L
Soil		50 mg/kg
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		3.39 µg/L
Freshwater sediment		27 µg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L

Soil	10 µg/kg
Titan dioxide > 10µm	
<b>Route of exposure:</b>	<b>Duration of Exposure:</b> <b>PNEC:</b>
Freshwater	- 0,184 mg/l
Freshwater sediment	- 1000 mg/l
Intermittent release	- 0,193 mg/l
Marine water	- 0,0184 mg/l
Marine water sediment	- 100 mg/Kg
Sewage treatment plant	- 100 mg/l
Soil	- 100 mg/l

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

Wash hands after use.

### Measures to avoid environmental exposure

No specific requirements.


## Individual protection measures, such as personal protective equipment

### Generally


In the event the work process is within scope of the Danish statutory order on work with code numbered products (Work Inspectorate Order no. 302/1993), then personal protection equipment shall be selected as set out herein. If applicable, please refer to the code number of this product in section 15.

Use only CE marked protective equipment.

### Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
Non industrial spraying	Combination filter A2P2	Class 2	Brown/White	EN14387	

### Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	

### Hand protection



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 240	EN374-2, EN16523-1, EN388



#### Eye protection

No specific requirements.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Various colours

#### Odour / Odour threshold

Faint

#### pH

8 - 9

#### Density (g/cm<sup>3</sup>)

1,20

#### Kinematic viscosity

No data available.

#### Particle characteristics

Does not apply to liquids.

#### Phase changes

##### Melting point/Freezing point (°C)

No data available.

##### Softening point/range (°C)

Does not apply to liquids.

##### Boiling point (°C)

No data available.

##### Vapour pressure

No data available.

##### Relative vapour density

No data available.

##### Decomposition temperature (°C)

No data available.

#### Data on fire and explosion hazards

##### Flash point (°C)

No data available.

##### Flammability (°C)

No data available.

##### Auto-ignition temperature (°C)

No data available.

##### Lower and upper explosion limit (% v/v)

No data available.

#### Solubility

##### Solubility in water

Completely soluble

##### n-octanol/water coefficient (LogKow)

No data available.

#### Solubility in fat (g/L)

No data available.

#### 9.2. Other information

##### VOC (g/L)

25

##### Other physical and chemical parameters

No data available.

##### Oxidizing properties

No data available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Product/substance	Titan dioxide > 10µm
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/Kg ·

Product/substance	Titan dioxide > 10µm
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 3,43 - 5,09 mg/l ·

Product/substance	propane-1,2-diol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	22000 mg/kg ·

Product/substance	propane-1,2-diol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	2000 mg/kg ·

Product/substance	propane-1,2-diol
Species:	Rabbit

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Route of exposure: Inhalation  
Test: LC50  
Result: 317 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: 1193 mg/Kg ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Rat  
Route of exposure: Dermal  
Test: LD50  
Result: 4115 mg/Kg ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
Species: Rabbit  
Route of exposure: Dermal  
Test: LD50  
Result: 210 mg/kg ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
Species: Rabbit  
Route of exposure: Oral  
Test: LD50  
Result: 300 mg/kg ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
Species: Rat  
Route of exposure: Inhalation  
Test: LC50  
Result: 2,21 mg/l/4h ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: > 200 -< 2000 mg/kg ·

Based on available data for the mixture, the classification criteria are not met.

#### Skin corrosion/irritation

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Test method: OECD 404  
Species: Rabbit  
Result: Adverse effect observed (Irritating)

Based on available data for the mixture, the classification criteria are not met.

#### Serious eye damage/irritation

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Test method: no guideline followed  
Result: Adverse effect observed (Causes serious eye damage)

Based on available data for the mixture, the classification criteria are not met.

#### Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

#### Skin sensitisation

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Human

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Result: Adverse effect observed (sensitising)  
Other information: Can course allergic reaction at skin contact

Product/substance: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
Test method: OECD 406  
Other information: Can course allergic reaction at skin contact

This product contains substances that may trigger an allergic reaction in already sensitized persons.

#### Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

#### Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

#### Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

#### STOT-single exposure

Based on available data for the mixture, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.

#### Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

#### 11.2. Information on other hazards

##### Long term effects

None known.

##### Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

##### Other information

None known.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance: Titan dioxide > 10µm  
Species: Fish  
Duration: 96 hours  
Test: LC50  
Result: >1000 mg/l ·

Product/substance: Titan dioxide > 10µm  
Species: Daphnia  
Duration: 48 hours  
Test: EC50  
Result: >1000 mg/l ·

Product/substance: Titan dioxide > 10µm  
Species: Algae  
Duration: 72 hours  
Test: EC50  
Result: 61 mg/l ·

Product/substance: propane-1,2-diol  
Species: Fish  
Duration: 96 hours  
Test: LC50  
Result: > 40613 mg/l ·

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance propane-1,2-diol  
Species: Daphnia  
Duration: 48 hours  
Test: EC50  
Result: 18800 mg/l ·

Product/substance propane-1,2-diol  
Species: Algae  
Duration: 96 hours  
Test: EC50  
Result: 19000 mg/l ·

Product/substance propane-1,2-diol  
Species: Algae  
Duration: 72 hours  
Test: EC50  
Result: 24200 mg/l ·

Product/substance ammonia ....%  
Species: Fish  
Duration: 96 hours  
Test: LC50  
Result: 0,89 mg/l ·

Product/substance ammonia ....%  
Species: Daphnia  
Duration: 48 hours  
Test: LC50  
Result: 101 mg/l ·

Product/substance ammonia ....%  
Species: Algae  
Duration: 18 d.  
Test: EC50  
Result: 2700 mg/l ·

Product/substance ammonia ....%  
Species: Fish  
Duration: 73 d.  
Test: LOEC  
Result: 0,022 mg/l ·

Product/substance ammonia ....%  
Species: Daphnia  
Duration: 96 hours  
Test: NOEC  
Result: 0,79 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Fish  
Duration: 96 hours  
Test: LC50  
Result: 1,3 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Daphnia  
Duration: 96 hours  
Test: EC50

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Result: 1,5 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Algae  
Duration: 48 hours  
Test: EC50  
Result: 0,055 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Daphnia  
Duration: 48 hours  
Test: EC50  
Result: 2,94 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Algae  
Duration: 24 hours  
Test: EC50  
Result: 0,11 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Fish  
Duration: No data available.  
Test: NOEC  
Result: 0,21 mg/l ·

Product/substance 1,2-benzisothiazol-3(2H)-one;  
Species: Daphnia  
Duration: 21 days  
Test: NOEC  
Result: 1,2 mg/l ·

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
Test method: OECD 201  
Species: Algae, *Pseudokirchneriella subcapitata*  
Compartment: Water  
Duration: 72 hours  
Test: EC50  
Result: 0,048 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
Test method: OECD 202  
Species: Daphnia, *Daphnia magna*  
Compartment: Water  
Duration: 48 hours  
Test: EC50  
Result: 0,1 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
Test method: OECD 201  
Species: Algae, *Skeletonema costatum*  
Compartment: Water  
Duration: 48 hours  
Test: EC50  
Result: 0,0052 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
Test method: OECD 203

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Species: Fish, *Oncorhynchus mykiss*  
 Compartment: Water  
 Duration: 96 hours  
 Test: LC50  
 Result: 0,22 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Test method: OECD 211  
 Species: *Daphnia*, *Daphnia magna*  
 Compartment: Water  
 Duration: 21 days  
 Test: NOEC  
 Result: 0,004 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Test method: OECD 215  
 Species: Fish, *Oncorhynchus mykiss*  
 Compartment: Water  
 Duration: 28 days  
 Test: NOEC  
 Result: 0,098 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Test method: OECD 209  
 Compartment: Sewage treatment plant  
 Duration: 3 hours  
 Test: EC50  
 Result: 7,92 mg/L

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
 Species: Fish  
 Duration: 96 hours  
 Test: LC50  
 Result: 820 - 1490 mg/l ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
 Species: *Daphnia*  
 Duration: 48 hours  
 Test: EC50  
 Result: 835 - 1550 mg/l ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether  
 Species: Algae  
 Duration: 72 hours  
 Test: IC50  
 Result: 1840 mg/l ·

Based on available data for the mixture, the classification criteria are not met.

## 12.2. Persistence and degradability

Product/substance propane-1,2-diol  
 Result: BOD5/COD > 0,5  
 Conclusion: Readily biodegradable

Product/substance 1,2-benzisothiazol-3(2H)-one;  
 Conclusion: Readily biodegradable

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Result: 60 %  
 Conclusion: -

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Test: OECD 301 D

Product/substance: 2-butoxyethanol; ethylene glycol monobutyl ether  
Result: 88% after 28 dage  
Conclusion: Readily biodegradable  
Test: OECD 301 C

### 12.3. Bioaccumulative potential

Product/substance: propane-1,2-diol  
BCF: 0,09  
LogKow: -1,4000  
Conclusion: No potential for bioaccumulation

Product/substance: ammonia ....%  
LogKow: -0,6400  
Conclusion: -

Product/substance: 1,2-benzisothiazol-3(2H)-one;  
LogKow: 1,3000  
Conclusion: No potential for bioaccumulation

Product/substance: 2-butoxyethanol; ethylene glycol monobutyl ether  
BCF: 2,5  
LogKow: 0,8000  
Conclusion: No potential for bioaccumulation

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.  
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

#### EWC code

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

#### Specific labelling

Not applicable.

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information: n:
ADR	-	-	-	-	-	-



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Restrictions for application

No special.

##### Demands for specific education

No specific requirements.

##### SEVESO - Categories / dangerous substances

Not applicable.

##### Regulation on work involving coded products

Code number (1993): 00-1

##### Additional information

Not applicable.

##### Sources

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products.

Executive Order no. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car repair painting.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H311, Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H331, Toxic if inhaled.  
H335, May cause respiratory irritation.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.  
H411, Toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

Not applicable.

#### The safety data sheet is validated by

MIJ

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

Country-language: DK-en