

Product Description

Water based alkyd paint for windows with high solid content and excellent coverage.

Contains materials, that protect the film against surface mold.

Directions for use

It is recommended that the surface is firm, clean and dry (max. wood moisture 20%) and no chalking. Any resinous secretions should be removed with appropriate thinner. Do not carry out the application at temperatures below +10 ° C.

If it is necessary that the subject must be impregnated use an appropriate Wood preserver.

Apply two to three coats for durable, attractive finish.

Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

Safety & environment

Brush / Roller: Working close, PU-gloves and protective glass.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

Moisture content of the windows must be 12 + - 3% in freestanding wood and ventilated cladding max. 18%.

Technical data

Binder: Alkyd emulsion

Type:

Gloss:

Vol. dry: Approx 45%

Colours: White and Clear. Can be tinted

Drying: App. 2-4 hours at 20° C. RH.: 65%. Recoatable after app. 8 hours.

Application: +10 °C to + 25° C. RH: 40-80%

Thinning: Water

Coverage: Rough saw timber: 2-5 m²/Liter

Planed timber: 8-10 m²/Liter

Tools:

Mal-Code: 00-1 (1993)

