

Product Description

Semi-gloss alkyd oil paint especially suitable for windows and other woodwork outdoors. The Paint has very strong and, washable surface. That makes it highly suitable for applications where both the aesthetic as well as functional portion must be present.

Contains materials, that protect the film against surface mold..

Directions for use

The substrate must be clean, dry and sustainable and glossy surfaces sanded matt. Resin and knots should be degreased with appropriate solvent.

New bare wood primed with an appropriate priming oil against rot and mold, followed by one layer Cover-It diluted by 15-20% white spirit followed by one layer Cover-It diluted by 15-20% white spirit and then finished with 2-3 times Cover-It 875 undiluted.

Ferrous metals should be properly primed with an appropriate primer before painting with Cover-It 875.

Cleaning instructions

White Spirit or "Brush Cleaner"

Safety & environment

Brush / Roller: Working close, Nitrill-gloves and protective glass and A2 mask.

Spray: Protective clothing, PU-gloves and shield. A2P3 mask, with air supply when needed.

Sanding: Working clothes, PU-gloves and protective glass. P2 mask with air supply when needed.

Further information and MSDS on www.bj.dk

Remarks

The moisture content of windows and doors should be 12 +/- 3%.

By retreatment interval of more than five days, the surface should be sanded to ensure adhesion.

The product should not be applied in too thick film layers, as it may cause surface drying.

Technical data

Binder:	Alkyd oil
Type:	Alkydoil paint
Gloss:	Approx. 50 semi-gloss
Vol. dry:	App. 65%
Colours:	White and B&J tinting system
Drying:	6-8 hours, recoatable after 24 hours at 20 ° C 65% RH
Application:	+5° C to +25° C. RF: 40-80%
Thinning:	White spirit
Coverage:	Rough saw timber: 2-5 m ² /Liter Planed timber: 8-10 m ² /Liter
Tools:	Brush
Mal-Code:	2-1 (1993)

