

Product Description

Water-based, opaque primer based on pure acrylic binder for interior wood and wood-based materials.

Product characteristics:

- Inhibiting properties for water-soluble ingredients
- Good adhesion
- Good hiding power and fullness
- Quick and easy to sand

Directions for use

Surface must be clean, firm and sustainable. Wood moisture should not exceed 20% RH.

Any resin exudations to be removed and be after dried with an appropriate thinner.

The product is thoroughly stirred before and during use. Optionally diluted with water to spraying viscosity.

Need to be over coated with 976 DK Interior T236.

Recommended wet filmthickness: App. 150 micron.

Cleaning instructions

Clean with water immediately after use. Once a week clean the equipment using an appropriate cleaning agent.

Safety & environment

Personal protection equipment must be used. For information regarding safety, health and environment see Material Safety Data Sheet (MSDS) at www.bj.dk.

Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless	0,28 mm	150 bar		100 Mesh
Airmix	0,28 mm	80-90 bar	1-2 bar	100 Mesh
HVLP usw.	0,28 mm	80-90 bar	1-2 bar	100 Mesh

Technical data

Binder: Acrylic

Type:

Gloss: Approx. 3 Flat matt

Vol. dry: Approx. 40%

Colours: Off White

Drying: Sanding and recoatable: 2-3 hours at +20 °C og 65% RF

Application: Optimum temperature for the product, subject and location: 18-22 °C and R/F approx. 50%

Thinning: Water. Normally not to be diluted

Coverage: 6-8 m². Wet film 125-150 µm

Tools: Airless or Airmix. Optimal RF approx. 50%

Mal-Code: 00-1 (1993)

